

280 liters tank i rustfritt stål 304



61 000 SEK /st exkl moms

Article type: second-hand pressure tank

Volumetric volume (L): 280 L

Pressure in tank: pressure

Design pressure (Bar): 3,80 Bar

Max. pressure (Bar): 2,50 Bar

Material wet parts: SS AISI 304 (V2A)

Model: vertical

Configuration: insulated

Heat exchanger: no

Insulation: yes



Mobile tank: no

Shape of tank: cylindrical

Bottom type: dished

Total discharge: yes

Fixation points: 3 adjustable feet

Outer jacket (ornamental wall): RVS 304

Spray ball: RVS 304

Gasket manway(s): unknown

Fixation point(s): RVS 304

Suitable for food industry: yes

Documents included: no

Technical drawing included: no

Registration plate on the tank: yes

Flange for agitator: no

Number of manways: 1

Position of manway: at the top

Height manhole 1 (mm): 600 mm

CIP spray ball: yes

Tank outlet: inside Ø 32 mm

Outlet type: 32

Total outlet valve: yes

Internal diameter tank: 600 mm

Distance from outlet to ground: 280 mm

Outer diameter tank: 780 mm

Cylinder height: 1.000 mm

Empty weight tank: 250

SKU: 381116



Mer information

Beskrivelse av produkt

Næringsmiddelgodkjent: Ja
Materiale: Rustfritt stål 304
Modell: Vertikal
Nyprodusert/Brukt: Brukt
Arbeidstrykk i tank: trykk
Designtrekk for tanken: 3,80 bar
Konfiguration: isolert
Mobil tank: Nei, det er det ikke.
Omrører: Nei
Overtrykk: 2,50 bar
Tankens form: sylindrisk
Total uttapping:
Type bunn: tallerken
Trykktank: Ja
Oppvarming/kjøling: Nei
Væskebelastet overflate: SS AISI 304 (V2A)
Volum i liter: 280

Utstyr

Dokument finnes: Nei, det er det ikke.
Flens for omrører: Nei
Merkeskilt: Ja
Næringsmiddelgodkjent: Ja
Tankutløp: innvendig Ø 32 mm
Teknisk tegning finnes: Nei, det er det ikke.
Utløpstype: 32
Utløpsventil: Ja



Materialoversikt

Materiale: Rustfritt stål 304
Festepunkt(er): RVS 304
Utvendig kledning: RVS 304

Tankdimensjoner

Sylinderhøyde: 1 000 mm
Innvendig diameter: 600 mm
Mål utløp til bakken: 280 mm
Ytre diameter: 780 mm

Mer

Isolert: Ja
Vekt: 250