

29000 liters tank i syrefast 316



238 000 SEK /st exkl moms

Additional information: Cosmetics; Storage tank was manufactured according to WHG guidelines (WHG certificate available); Wall thickness cylinder: lower half 4 mm; upper half: 3 mm; Screws for mounting load cells (no longer available) under the base plates; 1 dent in the transition cylinder / lower bottom (see photos)

Volumetric volume (L): 29.000 L

Pressure in tank: ATM - atmospheric



Max. temperature (°C): 98 °C

Material wet parts: SS AISI 316 (V4A)

Model: vertical

Configuration: single-skin

Heat exchanger: no

Insulation: no

Mobile tank: no

Total discharge: yes

Documents included: no

Technical drawing included: no

Registration plate on the tank: yes

Flange for agitator: no

Position of manway: cylinder

Outlet of tank: 100

Top: 5 mm

Bottom: 8 mm

Internal diameter tank: 2.800 mm

Cylinder height: 4.000 mm

Total height of tank: 6.500 mm

SKU: 420452

Mer information



Beskrivelse av produkt

Materiale: Syrefast 316

Modell: Vertikal

Nyprodusert/Brukt: Brukt

Arbeidstrykk i tank:

Konfiguration: enkelthudet

Maks. arbeidstemperatur: 98 °C

Mobil tank: Nei, det er det ikke.

Øvrig informasjon:

Øvrig informasjon2: lenger tilgjengelig) under bunnplatene; 1 bulk i overgangssylinderen / nedre bunn (se bilder)

Omrører: Nei

Total uttapping:

Oppvarming/kjøling: Nei

Væskebelastet overflate: SS AISI 316 (V4A)

Volum i liter: 29000

Utstyr

Dokument finnes: Nei, det er det ikke.

Flens for omrører: Nei

Merkeskilt: Ja

Teknisk tegning finnes: Nei, det er det ikke.

Materialoversikt

Materiale: Syrefast 316

Tankdimensjoner

Sylinderhøyde: 4 000 mm

Innvendig diameter: 2 800 mm

Total høyde: 6 500 mm

Tanktykkelse

Bunn: 8 millimeter

Topp: 5 mm

Mer

Isolert: Nei