3000 liters tank i rustfritt stål 304

160 000 SEK /st exkl moms

Article type: second-hand mixing tank
Additional information: we can't give any guarantees about the agitator
Volumetric volume (L): 3.000 L
Pressure in tank: ATM - atmosferic

PROCESSÖVERSKOTT AB

Rodervägen 57
891 78 Bonässund
info@processoverskott.se

Läs våra köpvillkor

Material wet parts: SS AISI 304 (V2A)

Model: vertical
Configuration: insulated
Heat exchanger: no
Insulation: no
Mobile tank: no

Top type: conical
Shape of tank: cylindrical
Bottom type: conical
Total discharge: yes
Fixation points: 3 adjustable feet

Outer jacket (ornamental wall): RVS 304
Spray ball: RVS 304
Manway(s): RVS 304
Gasket manway(s): unknown
Fixation point(s): RVS 304

Suitable for food industry: yes
Documents included: no
Technical drawing included: no
Registration plate on the tank: no
Flange for agitator: no

Number of manways: 1
Position of manway: at the top
Agitator: yes
Agitator type: propeller agitator
Position engine: at the top

Internal diameter tank: 1.200 mm
Outer diameter tank: 1.300 mm
Total height of tank: 4.800 mm

SKU: 489375

PROCESSÖVERSKOTT AB

Rodervägen 57
891 78 Bonässund
info@processoverskott.se

Läs våra köpvillkor

Mer information

Beskrivelse av produkt

Næringsmiddelgodkjent: Ja
Materiale: Rustfritt stål 304
Modell: Vertikal
Nyprodusert/Brukt: Brukt
Arbeidstrykk i tank:
Konfiguration: isolert
Mobil tank: Nei, det er det ikke.
Øvrig informasjon: vi kan ikke gi noen garantier for omrøreren
Omrører: Ja
Tankens form: sylindrisk
Total uttapping:
Type bunn: konisk
Oppvarming/kjøling: Nei
Væskebelastet overflate: SS AISI 304 (V2A)
Volum i liter: 3000

Utstyr

Dokument finnes: Nei, det er det ikke.
Flens for omrører: Nei
Merkeskilt: Nei, det er det ikke.
Næringsmiddelgodkjent: Ja
Teknisk tegning finnes: Nei, det er det ikke.

Materialoversikt

Materiale: Rustfritt stål 304
Festepunkt(er): RVS 304
Utvendig kledning: RVS 304

Rodervägen 57
891 78 Bonässund
info@processoverskott.se

Tankdimensjoner
Innvendig diameter: 1 200 mm
Total høyde: 4 800 mm
Ytre diameter: 1 300 mm

Omrører
Motorposisjon: på toppen
Type omrører: propellomrører

Mer
Isolert: Nei

PROCESSÖVERSKOTT AB

Rodervägen 57
891 78 Bonässund
info@processoverskott.se

Läs våra köpvillkor