3000 liters tank i rustfritt stål 304

107 000 SEK /st exkl moms

Article type: second-hand mixing tank
Additional information: we can't give any guarantees about the heating/cooling jacket; we can't give any guarantees about the agitator
Volumetric volume (L): 3.000 L
Pressure in tank: ATM - atmosferic
Material wet parts: SS AISI 304 (V2A)

Model: vertical
Configuration: insulated with heat-exchanger
Heat exchanger: yes
Insulation: yes

PROCESSÖVERSKOTT AB

Rodervägen 57
891 78 Bonässund
info@processoverskott.se

Läs våra köpvillkor

Mobile tank: no

Top type: conical
Shape of tank: cylindrical
Bottom type: conical
Bottom outlet: yes
Total discharge: yes

Fixation points: 3 adjustable feet
Type of HE on the cylinder: half pipe welded onto the outside of the innertank
Position HE: the complet cilinder
Type of HE on the bottom: half pipe welded onto the outside of the innertank
Manway(s): RVS 304

Gasket manway(s): unknown
Fixation point(s): RVS 304
Suitable for food industry: yes
Documents included: no
Technical drawing included: no

Registration plate on the tank: no
Flange for agitator: no
Position of manway: at the top
Height manhole 1 (mm): 350 mm x H 440 mm
Hinged lid: yes

Tank outlet: inside Ø 50 mm
Agitator: yes
Agitator type: propeller agitator
Position engine: at the top
Power: 2

Voltage: 380 V - three-phase
Current: 3,70
Distance from outlet to ground: 700 mm
Outer diameter tank: 1.700 mm
Cylinder height: 1.650 mm

Total height of tank: 3.000 mm

PROCESSÖVERSKOTT AB

Rodervägen 57
891 78 Bonässund
info@processoverskott.se

Läs våra köpvillkor

Empty weight tank: 900

SKU: 416822

Mer information

Beskrivelse av produkt

Næringsmiddelgodkjent: Ja
Materiale: Rustfritt stål 304
Modell: Vertikal
Nyprodusert/Brukt: Brukt
Arbeidstrykk i tank: ATM – atmosfærisk
Konfiguration: isolert med varmeveksler
Mobil tank: Nei, det er det ikke.
Øvrig informasjon: vi kan ikke gi noen garantier for varme-/kjølekappen; vi kan ikke gi noen garantier for omrøreren
Omrører: Ja
Tankens form: sylindrisk
Total uttapping: Ja
Type bunn: konisk
Oppvarming/kjøling: Ja
Væskebelastet overflate: SS AISI 304 (V2A)
Volum i liter: 3000

PROCESSÖVERSKOTT AB

Rodervägen 57
891 78 Bonässund
info@processoverskott.se

Läs våra köpvillkor

Utstyr

Dokument finnes: Nei, det er det ikke.
Flens for omrører: Nei
Merkeskilt: Nei, det er det ikke.
Næringsmiddelgodkjent: Ja
Tankutløp: innvendig Ø 50 mm
Teknisk tegning finnes: Nei, det er det ikke.

Materialoversikt

Materiale: Rustfritt stål 304
Festepunkt(er): RVS 304

Tankdimensjoner

Sylinderhøyde: 1 650 mm
Mål utløp til bakken: 700 mm
Total høyde: 3 000 mm
Ytre diameter: 1 700 mm

Varmevekslere

Posisjon varmeveksler: den komplette sylinderen
Type varmeveksler på sylinder: halvrør sveiset på utsiden av innertanken
Type varmeveksler på bunn: halvrør sveiset på utsiden av innertanken

Omrører

Effekt (kW): 2
Motorposisjon: på toppen
Type omrører: propellomrører
Spenning (Volt): 380 V – trefase

Mer

Isolert: Ja
Vekt: 900

Rodervägen 57
891 78 Bonässund
info@processoverskott.se