

3000 liters tank i syrefast 316



57 000 SEK /st exkl moms

Additional information: Cip-tank; Several pipes inside the tank (see photos)

Volumetric volume (L): 3.000 L

Pressure in tank: ATM - atmosferic

Max. temperature (°C): 80 °C



Material wet parts: SS AISI 316 (V4A)

Model: vertical

Configuration: single-skin

Heat exchanger: no

Insulation: no

Mobile tank: no

Total discharge: yes

Documents included: no

Technical drawing included: no

Registration plate on the tank: yes

Flange for agitator: no

Position of manway: in the bottom

Outlet of tank: flange DN150

Cylinder: 3 mm

Bottom: 4 mm

Internal diameter tank: 1.500 mm

Cylinder height: 1.700 mm

Total height of tank: 2.900 mm

SKU: 402914

Mer information



Beskrivelse av produkt

Materiale: Syrefast 316

Modell: Vertikal

Nyprodusert/Brukt: Brukt

Arbeidstrykk i tank: ATM – atmosfærisk

Konfiguration: enkelthudet

Maks. arbeidstemperatur: 80 °C

Mobil tank: Nei, det er det ikke.

Øvrig informasjon: Cip-tank; Flere rør inne i tanken (se bilder)

Omrører: Nei

Total uttapping: Ja

Oppvarming/kjøling: Nei

Væskebelastet overflate: SS AISI 316 (V4A)

Volum i liter: 3000

Utstyr

Dokument finnes: Nei, det er det ikke.

Flens for omrører: Nei

Merkeskilt: Ja

Teknisk tegning finnes: Nei, det er det ikke.

Materialoversikt

Materiale: Syrefast 316

Tankdimensjoner

Sylinderhøyde: 1 700 mm

Innvendig diameter: 1 500 mm

Total høyde: 2900 mm

Tanktykkelse

Bunn: 4 mm

Sylinder: 3 mm



Mer

Isolert: Nei