

3000 liters tank i syrefast 316



75 000 SEK /st exkl moms

Additional information: 500 mm manhole in the front bottom

Volumetric volume (L): 3.000 L

Pressure in tank: pressure and vacuum

Max. pressure (Bar): 2 Bar



Min. pressure (Bar): 1 Bar

Max. temperature (°C): 100 °C

Material wet parts: SS AISI 316 (V4A)

Model: horizontal

Configuration: single-skin

Heat exchanger: no

Insulation: no

Mobile tank: no

Total discharge: yes

Documents included: no

Technical drawing included: no

Registration plate on the tank: yes

Flange for agitator: no

Outlet of tank: flange DN50

Internal diameter tank: 1.385 mm

Total height of tank: 1.960 mm

Total outer length: 2.830 mm

Empty weight tank: 900

SKU: 488211

Mer information



Beskrivelse av produkt

Materiale: Syrefast 316
Modell: Horisontal
Nyprodusert/Brukt: Brukt
Arbeidstrykk i tank: trykk og vakuum
Konfiguration: enkelthudet
Maks. arbeidstemperatur: 100 °C
Mobil tank: Nei, det er det ikke.
Øvrig informasjon: 500 mm mannhull i bunnen foran
Omrører: Nei
Overtrykk: 2 barer
Total uttapping: Ja
Undertrykk (vakuum): 1 bar
Trykktank: Ja
Oppvarming/kjøling: Nei
Væskebelastet overflate: SS AISI 316 (V4A)
Volum i liter: 3000

Utstyr

Dokument finnes: Nei, det er det ikke.
Flens for omrører: Nei
Merkeskilt: Ja
Teknisk tegning finnes: Nei, det er det ikke.

Materialoversikt

Materiale: Syrefast 316

Tankdimensjoner

Innvendig diameter: 1385 mm
Total høyde: 1 960 mm



Mer

Isolert: Nei

Vekt: 900