



30000 liters tank i rustfritt stål 304



295 000 SEK /st exkl moms

Article type: second-hand mixing tank

Additional information: 2 tanks with agitator, 1 tank without agitator; we can't give any guarantees about the agitator

Volumetric volume (L): 30.000 L

Pressure in tank: ATM - atmosferic

Material wet parts: SS AISI 304 (V2A)

Model: vertical

Configuration: insulated

Heat exchanger: no

Insulation: yes

Mobile tank: no

Top type: conical

Shape of tank: cylindrical

Bottom type: conical

Total discharge: yes

Fixation points: 6 adjustable feet

Outer jacket (ornamental wall): RVS 304

Manway(s): RVS 304

Fixation point(s): RVS 304

Suitable for food industry: yes

Documents included: no

Technical drawing included: no

Registration plate on the tank: yes

Flange for agitator: no

Number of manways: 1



Position of manway: at the top

Agitator: yes

Agitator type: tripad

Position engine: at the top

Number of revolutions: 20

Power: 4,25

Voltage: three-phase

Internal diameter tank: 2.900 mm

Distance from outlet to ground: 500 mm

Outer diameter tank: 3.000 mm

Cylinder height: 4.650 mm

Feet height: 1.000 mm

Total height of tank: 6.700 mm

Empty weight tank: 2.600

SKU: 383618

Mer information



Beskrivelse av produkt

Næringsmiddelgodkjent: Ja

Materiale: Rustfritt stål 304

Modell: Vertikal

Nyprodusert/Brukt: Brukt

Arbeidstrykk i tank: ATM – atmosfærisk

Konfiguration: isolert

Mobil tank: Nei, det er det ikke.

Øvrig informasjon: 2 tanker med røreverk, 1 tank uten røreverk; vi kan ikke gi noen garantier for røreverket

Omrører: Ja

Tankens form: sylindrisk

Total uttapping: Ja

Type bunn: konisk

Oppvarming/kjøling: Nei

Væskebelastet overflate: SS AISI 304 (V2A)

Volum i liter: 30000

Utstyr

Dokument finnes: Nei

Flens for omrører: Nei

Merkeskilt: Ja

Næringsmiddelgodkjent: Ja

Teknisk tegning finnes: Nei, det er det ikke.

Materialoversikt

Materiale: Rustfritt stål 304

Festepunkt(er): RVS 304

Utvendig kledning: RVS 304



Tankdimensjoner

Sylinderhøyde: 4 650 mm
Høyde på ben: 1 000 mm
Innvendig diameter: 2900 mm
Mål utløp til bakken: 500 mm
Total høyde: 6 700 mm
Ytre diameter: 3 000 mm

Omrører

Effekt (kW): 4,25
Motorposisjon: på toppen
Type omrører: tripad
Turtall: 20
Spenning (Volt): trefaset

Mer

Isolert: Ja
Vekt: 2.600