30000 liters tank i rustfritt stål 304

294 000 SEK /st exkl moms

Article type: second-hand mixing tank
Additional information: 2 tanks with agitator, 1 tank without agitator; we can't give any guarantees about the agitator
Volumetric volume (L): 30.000 L
Pressure in tank: ATM - atmosferic

PROCESSÖVERSKOTT AB

Rodervägen 57
891 78 Bonässund
info@processoverskott.se

Läs våra köpvillkor

Material wet parts: SS AISI 304 (V2A)

Model: vertical
Configuration: insulated
Heat exchanger: no
Insulation: yes
Mobile tank: no

Top type: conical
Shape of tank: cylindrical
Bottom type: conical
Total discharge: yes
Fixation points: 6 adjustable feet

Outer jacket (ornamental wall): RVS 304
Manway(s): RVS 304
Fixation point(s): RVS 304
Suitable for food industry: yes
Documents included: no

Technical drawing included: no
Registration plate on the tank: yes
Flange for agitator: no
Number of manways: 1
Position of manway: at the top

Agitator: yes
Agitator type: tripad
Position engine: at the top
Number of revolutions: 20
Power: 4,25

Voltage: three-phase
Internal diameter tank: 2.900 mm
Distance from outlet to ground: 500 mm
Outer diameter tank: 3.000 mm
Cylinder height: 4.650 mm

Feet height: 1.000 mm
Total height of tank: 6.700 mm

Rodervägen 57
891 78 Bonässund
info@processoverskott.se

Empty weight tank: 2.600

SKU: 383657

Mer information

Beskrivelse av produkt

Næringsmiddelgodkjent: Ja
Materiale: Rustfritt stål 304
Modell: Vertikal
Nyprodusert/Brukt: Brukt
Arbeidstrykk i tank:
Konfiguration: isolert
Mobil tank: Nei, det er det ikke.
Øvrig informasjon: 2 tanker med røreverk, 1 tank uten røreverk; vi kan ikke gi noen garantier for røreverket
Omrører: Ja
Tankens form: sylindrisk
Total uttapping:
Type bunn: konisk
Oppvarming/kjøling: Nei
Væskebelastet overflate: SS AISI 304 (V2A)
Volum i liter: 30000

Utstyr

Dokument finnes: Nei
Flens for omrører: Nei
Merkeskilt: Ja
Næringsmiddelgodkjent: Ja
Teknisk tegning finnes: Nei, det er det ikke.

Rodervägen 57
891 78 Bonässund
info@processoverskott.se

Materialoversikt

Materiale: Rustfritt stål 304
Festepunkt(er): RVS 304
Utvendig kledning: RVS 304

Tankdimensjoner

Sylinderhøyde: 4 650 mm
Høyde på ben: 1 000 mm
Innvendig diameter: 2900 mm
Mål utløp til bakken: 500 mm
Total høyde: 6 700 mm
Ytre diameter: 3 000 mm

Omrører

Effekt (kW): 4,25
Motorposisjon: på toppen
Type omrører: tripad
Turtall: 20
Spenning (Volt): trefaset

Mer

Isolert: Ja
Vekt: 2.600

PROCESSÖVERSKOTT AB

Rodervägen 57
891 78 Bonässund
info@processoverskott.se

Läs våra köpvillkor