

30000 liters tank i syrefast 316



170 000 SEK /st exkl moms

Article type: second-hand storage tank

Additional information: the conical top has slight deformation

Volumetric volume (L): 30.000 L

Max. density P (kg/m³): 1.000

Ra inner weld: 0,80

Pressure in tank: ATM - atmosferic

Material wet parts: SS AISI 316 (V4A)

Model: vertical

Configuration: single-skin

Heat exchanger: no



Insulation: no

Mobile tank: no

Top type: conical

Shape of tank: cylindrical

Bottom type: conical

Total discharge: yes

Fixation points: 4 adjustable feet

Manway(s): RVS 316

Gasket manway(s): unknown

Fixation point(s): RVS 304

Suitable for food industry: yes

Documents included: no

Technical drawing included: no

Registration plate on the tank: no

Flange for agitator: no

Number of manways: 1

Position of manway: cylinder

Height manhole 1 (mm): 320 mm x H 430 mm

Tank outlet: inside Ø 80 mm

Outlet type: DIN11851

Agitator: no, optional

Distance from outlet to ground: 350 mm

Outer diameter tank: 2.750 mm

Cylinder height: 5.050 mm

Total height of tank: 6.700 mm

Empty weight tank: 2.500

SKU: 481579



Mer information

Beskrivelse av produkt

Næringsmiddelgodkjent: Ja

Materiale: Syrefast 316

Modell: Vertikal

Nyprodusert/Brukt: Brukt

Arbeidstrykk i tank:

Konfiguration: enkelthudet

Maksimal tetthet for produktet: 1000

Mobil tank: Nei, det er det ikke.

Øvrig informasjon: den koniske toppen har en liten deformasjon

Omrører: Nei

Ra innvendig sveis: 0,80

Tankens form: sylindrisk

Total uttapping:

Type bunn: konisk

Oppvarming/kjøling: Nei

Væskebelastet overflate: SS AISI 316 (V4A)

Volum i liter: 30000

Utstyr

Dokument finnes: Nei, det er det ikke.

Flens for omrører: Nei

Merkeskilt: Nei, det er det ikke.

Næringsmiddelgodkjent: Ja

Tankutløp: innvendig Ø 80 mm

Teknisk tegning finnes: Nei, det er det ikke.

Utløpstype: DIN11851

Materialoversikt

Materiale: Syrefast 316

Festepunkt(er): RVS 304



Tankdimensjoner

Sylinderhøyde: 5 050 mm

Mål utløp til bakken: 350 mm

Total høyde: 6 700 mm

Ytre diameter: 2750 mm

Mer

Isolert: Nei

Vekt: 2.500