

32000 liters tank i 304 rustfritt stål



320 000 SEK /st exkl moms

Article type: second-hand storage tank

Additional information: The tank has never been used.

Volumetric volume (L): 32.000 L

Max. density P (kg/m³): 1.200

Ra inner weld: 0,80

Finish stainless steel: 2B

Pressure in tank: ATM - atmosferic

Max. temperature (°C): 60 °C

Min. temperature (°C): -10 °C

Material wet parts: SS AISI 304L (V2A)



Model: vertical

Configuration: single-skin

Heat exchanger: no

Insulation: no

Mobile tank: no

Top type: conical 13 °

Shape of tank: cylindrical

Bottom type: conical 20 °

Total discharge: yes

Fixation points: 4 non adjustable feet

Manway(s): RVS 304L

Gasket manway(s): EPDM

Fixation point(s): RVS 304L

Suitable for food industry: yes

Documents included: yes, optional

Technical drawing included: yes

Registration plate on the tank: yes

Flange for agitator: no

Number of manways: 1

Position of manway: at the top

Height manhole 1 (mm): 500 mm

Hinged lid: yes

Tank outlet: inside Ø 80 mm

Outlet type: DIN11851 male

Total outlet valve: no, optional

Top: 2 mm

Cylinder: 2 mm

Bottom: 4 mm

Distance from outlet to ground: 395 mm

Outer diameter tank: 2.984 mm

Cylinder height: 4.500 mm

Total height of tank: 5.872 mm

Empty weight tank: 1.250



SKU: 480507

Mer information

Beskrivelse av produkt

Næringsmiddelgodkjent: Ja

Materiale: Rustfritt stål 304

Modell: Vertikal

Nyprodusert/Brukt: Brukt

Arbeidstrykk i tank:

Finish rustfritt stål: 2b

Konfiguration: enkelthudet

Maks. arbeidstemperatur: 60 °C

Maksimal tetthet for produktet: 1200

Min. arbeidstemperatur: -10 °C

Mobil tank: Nei, det er det ikke.

Øvrig informasjon: Tanken har aldri vært i bruk.

Omrører: Nei

Ra innvendig sveis: 0,80

Tankens form: sylindrisk

Total uttapping:

Type bunn: konisk 20

Oppvarming/kjøling: Nei

Væskebelastet overflate: SS AISI 304L (V2A)

Volum i liter: 32000



Utstyr

Flens for omrører: Nei
Merkeskilt: Ja
Næringsmiddelgodkjent: Ja
Tankutløp: innvendig Ø 80 mm
Teknisk tegning finnes: Ja
Utløpstype: DIN11851 hann

Materialoversikt

Materiale: Rustfritt stål 304
Festepunkt(er): RVS 304L

Tankdimensjoner

Sylinderhøyde: 4500 mm
Mål utløp til bakken: 395 mm
Total høyde: 5 872 mm
Ytre diameter: 2 984 mm

Tanktykkelse

Bunn: 4 mm
Sylinder: 2 millimeter
Topp: 2 millimeter

Mer

Isolert: Nei
Vekt: 1.250