

32000 liters tank i syrefast 316



431 000 SEK /st exkl moms

Additional information: Diameter of manhole cylinder 500 mm (manhole cover screws mostly missing); one vessel has 1 foot, the other vessel has 2 feet pressed into the lower bottom (this vessel also has 1 connection pressed into the upper bottom and the heating coil is pressed in at one point); the pressed-in feet would have to be repaired on site before the tanks are reinstalled; external insulating rings made of Fe (partially slightly damaged); 1 vessel in the outlet with flanged reduction (inner pipe diameter approx. 55



mm); see photos; some residues of previous content; manhole cover plated

Volumetric volume (L): 32.000 L

Pressure in tank: pressure and vacuum

Max. pressure (Bar): 3 Bar

Min. pressure (Bar): 1 Bar

Max. temperature (°C): 200 °C

Material wet parts: SS AISI 316 (V4A)

Model: vertical

Configuration: single-skin

Heat exchanger: no

Insulation: no

Mobile tank: no

Total discharge: yes

Volume: 80 L

Max Overpressure: 6 Bar

Type HE on the bottom: half pipe welded onto the outside of the innertank

Documents included: no

Technical drawing included: no

Registration plate on the tank: yes

Flange for agitator: no

Outlet of tank: 100

Cylinder: 8 mm

Bottom: 10 mm

Internal diameter tank: 2.400 mm

Cylinder height: 6.970 mm

Total height of tank: 9.050 mm

Empty weight tank: 7.000

SKU: 429674



Mer information

Beskrivelse av produkt

Materiale: Syrefast 316

Modell: Vertikal

Nyprodusert/Brukt: Brukt

Arbeidstrykk i tank: trykk og vakuum

Konfiguration: enkeltmantlet med varmeveksler

Maks. arbeidstemperatur: 200 °C

Mobil tank: Nei, det er det ikke.

Øvrig informasjon: Kjemisk; Sylinderdiameter på kumlukk 500 mm (de fleste skruene på kumlukket mangler); 1 tank har 1 fot presset inn i den nedre bunnen og den andre tanken har 2 føtter presset inn i den nedre

Omrører: Nei

Overtrykk: 3 barer

Total uttapping:

Undertrykk (vakuum): 1 bar

Trykktank: Ja

Oppvarming/kjøling: Ja

Væskebelastet overflate: SS AISI 316 (V4A)

Volum i liter: 32000

Utstyr

Dokument finnes: Nei, det er det ikke.

Flens for omrører: Nei

Merkeskilt: Ja

Teknisk tegning finnes: Nei, det er det ikke.

Materialoversikt

Materiale: Syrefast 316



Tankdimensjoner

Sylinderhøyde: 6 970 mm

Innvendig diameter: 2 400 mm

Total høyde: 9 050 mm

Tanktykkelse

Bunn: 10 mm

Sylinder: 8 millimeter

Mer

Isolert: Nei

Vekt: 7.000