

35000 liters tank i syrefast 316



206 000 SEK /st exkl moms

Article type: second-hand storage tank

Additional information: Equipped with 1 compartment.

Volumetric volume (L): 35.000 L

Pressure in tank: ATM - atmosferic

Material wet parts: SS AISI 316L (V4A)

Model: horizontal

Configuration: single-skin

Heat exchanger: no

Insulation: no

Mobile tank: no

Shape of tank: cylindrical

Wall type: dished

Total discharge: yes

Fixation points: saddles



Manway(s): RVS 316

Gasket manway(s): unknown

Fixation point(s): steel-epoxy

Suitable for food industry: yes

Documents included: no

Technical drawing included: no

Registration plate on the tank: yes

Flange for agitator: no

Number of manways: 3

Position of manway: at the top

Height manhole 1 (mm): 500 mm

Position 2nd manway: at the top

Height manhole 2 (mm): 500

CIP spray ball: no

Tank outlet: inside Ø 80 mm

Total outlet valve: yes

Agitator: no

Top: 5 mm

Cylinder: 5 mm

Bottom: 5 mm

Outer diameter tank: 2.500 mm

Total height of tank: 2.950 mm

Total outer length: 8.400 mm

Empty weight tank: 6.000

SKU: 378077



Mer information

Beskrivelse av produkt

Næringsmiddelgodkjent: Ja
Materiale: Syrefast 316
Modell: Horisontal
Nyprodusert/Brukt: Brukt
Arbeidstrykk i tank:
Konfiguration: enkelthudet
Mobil tank: Nei, det er det ikke.
Øvrig informasjon: Utstyrt med 1 rom.
Omrører: Nei
Tankens form: sylindrisk
Total uttapping:
Oppvarming/kjøling: Nei
Væskebelastet overflate: SS AISI 316L (V4A)
Volum i liter: 35000

Utstyr

Dokument finnes: Nei, det er det ikke.
Flens for omrører: Nei
Merkeskilt: Ja
Næringsmiddelgodkjent: Ja
Tankutløp: innvendig Ø 80 mm
Teknisk tegning finnes: Nei, det er det ikke.
Utløpsventil: Ja

Materialoversikt

Materiale: Syrefast 316
Festepunkt(er): stål-epoksy

Tankdimensjoner

Total høyde: 2 950 mm
Ytre diameter: 2 500 mm



Tanktykkelse

Bunn: 5 mm

Sylinder: 5 mm

Topp: 5 mm

Mer

Isolert: Nei

Vekt: 6.000