

3533 liter tank i rustfritt stål 304



110 000 SEK /st exkl moms

Additional information: Double jacket with electric plug-in heater : 9 kW (incomplete; no guarantee of functionality); presumably the lower cylinder area of the vessel can also be heated; manhole approx. 310 x 420 mm; internal fittings (e.g. welded tabs) inside the tank; some residues of previous content

Volumetric volume (L): 3.533 L

Pressure in tank: ATM - atmospheric



Max. temperature (°C): 50 °C

Material wet parts: SS AISI 304 (V2A)

Model: vertical

Configuration: insulated

Heat exchanger: no

Insulation: yes

Mobile tank: no

Total discharge: yes

Volume: 553 L

Max. working temperature: 50 °C

Type HE on the bottom: heating/cooling jacket

Heat exchanger: RVS 304

Documents included: no

Technical drawing included: no

Registration plate on the tank: yes

Flange for agitator: no

Position of manway: cylinder

Outlet of tank: DN50 DIN 11851

Agitator: yes

Number of revolutions: 76

Power: 1,50

Internal diameter tank: 1.490 mm

Outer diameter tank: 1.650 mm

Cylinder height: 1.980 mm

Total height of tank: 3.200 mm

SKU: 414359



Mer information

Beskrivelse av produkt

Materiale: Rustfritt stål 304

Modell: Vertikal

Nyprodusert/Brukt: Brukt

Arbeidstrykk i tank: ATM – atmosfærisk

Konfiguration: isolert med varmeveksler

Maks. arbeidstemperatur: 50 °C

Mobil tank: Nei, det er det ikke.

Øvrig informasjon: Apotek; Dobbel kappe med elektrisk plug-in-varmer: 9 kW (ufullstendig; funksjonalitet ikke garantert); antagelig kan også det nedre sylindrområdet i tanken varmes opp; mannhull ca. 310 x 420

Øvrig informasjon2:

Omrører: Ja

Total uttapping: Ja

Oppvarming/kjøling: Ja

Væskebelastet overflate: SS AISI 304 (V2A)

Volum i liter: 3533

Utstyr

Dokument finnes: Nei, det er det ikke.

Flens for omrører: Nei

Merkeskilt: Ja

Teknisk tegning finnes: Nei, det er det ikke.

Materialoversikt

Materiale: Rustfritt stål 304



Tankdimensjoner

Sylinderhøyde: 1 980 mm

Innvendig diameter: 1 490 mm

Total høyde: 3 200 mm

Ytre diameter: 1 650 mm

Omrører

Effekt (kW): 1,50

Turtall: 76

Mer

Varmeveksler: RVS 304

Isolert: Ja