3586 liters tank i syrefast 316

259 000 SEK /st exkl moms

Additional information: Pharmaceutical chemistry; Further technical documentation available; sight glass in manhole cover missing; support ring made of Fe; flanges partly made of Fe
Volumetric volume (L): 3.586 L
Pressure in tank: vacuum
Max. pressure (Bar): 3,20 Bar

PROCESSÖVERSKOTT AB

Rodervägen 57
891 78 Bonässund
info@processoverskott.se

Läs våra köpvillkor

Min. pressure (Bar): 1 Bar

Max. temperature (°C): 200 °C
Material wet parts: SS AISI 316 (V4A)
Model: vertical
Configuration: single-skin
Heat exchanger: no

Insulation: no
Mobile tank: no
Total discharge: no
Volume: 202 L
Max Overpressure: 16 Bar

Max onderdruk: 1 Bar
Max. working temperature: 200 °C
Type HE on the bottom: half pipe welded onto the outside of the innertank
Type HE on the cylinder: half pipe welded onto the outside of the innertank
Documents included: no

Technical drawing included: no
Registration plate on the tank: yes
Flange for agitator: no
Position of manway: headside
Agitator: yes

Number of revolutions: 6 - 40
Power: 3,50
Top: 9,10 mm
Cylinder: 6 mm
Bottom: 6,50 mm

Internal diameter tank: 1.600 mm
Cylinder height: 1.377 mm
Total height of tank: 4.250 mm

SKU: 406022

Rodervägen 57
891 78 Bonässund
info@processoverskott.se

Mer information

Beskrivelse av produkt

Materiale: Syrefast 316
Modell: Vertikal
Nyprodusert/Brukt: Brukt
Arbeidstrykk i tank: trykk og vakuum
Konfiguration: enkeltmantlet med varmeveksler
Maks. arbeidstemperatur: 200 °C
Mobil tank: Nei, det er det ikke.
Øvrig informasjon: Farmasøytisk kjemi; Ytterligere tekniske dokumenter tilgjengelig; Skueglass i kumlokk mangler; støttering, Fe; Flenser delvis laget av Fe; vi kan ikke gi noen garantier om
Øvrig informasjon2: omrører
Omrører: Ja
Overtrykk: 3,20 bar
Total uttapping: Nei, det er det ikke.
Undertrykk (vakuum): 1 bar
Trykktank: Ja
Oppvarming/kjøling: Ja
Væskebelastet overflate: SS AISI 316 (V4A)
Volum i liter: 3586

Utstyr

Dokument finnes: Nei, det er det ikke.
Flens for omrører: Nei
Merkeskilt: Ja
Teknisk tegning finnes: Nei, det er det ikke.

Materialoversikt

Materiale: Syrefast 316

Rodervägen 57
891 78 Bonässund
info@processoverskott.se

Tankdimensjoner
Sylinderhøyde: 1377 mm
Innvendig diameter: 1 600 mm
Total høyde: 4 250 mm

Omrører
Effekt (kW): 3,50
Turtall: 6 – 40

Tanktykkelse
Bunn: 6,50 mm
Sylinder: 6 millimeter
Topp: 9,10 mm

Mer
Isolert: Nei

PROCESSÖVERSKOTT AB

Rodervägen 57
891 78 Bonässund
info@processoverskott.se