

35895 liter tank i syrefast 316



295 000 SEK /st exkl moms

Article type: second-hand pressure tank

Volumetric volume (L): 35.895 L

Pressure in tank: pressure

Design pressure (Bar): 10 Bar

Max. pressure (Bar): 4 Bar

Max. temperature (°C): 50 °C

Material wet parts: SS AISI 316L (V4A)

Model: horizontal

Configuration: insulated

Heat exchanger: no



Insulation: no

Mobile tank: no

Shape of tank: cylindrical

Wall type: dished

Total discharge: yes

Fixation points: non adjustable feet

Insulation material: Rockwool

Outer jacket (ornamental wall): RVS 304L

Manway(s): RVS 316

Gasket manway(s): unknown

Valve: RVS 316L

Gasket shut-off valve (mat): unknown

Fixation point(s): painted steel

Suitable for food industry: no

Documents included: no

Technical drawing included: no

Registration plate on the tank: yes

Flange for agitator: no

Position of manway: at the top

Tank outlet: inside Ø 100 mm

Total outlet valve: yes

Top: 6 mm

Cylinder: 6 mm

Bottom: 6 mm

Insulation top: yes

Insulation body: yes

Insulation bottom/sides: yes

finish of the outer jacket: riveted

Insulation thickness: 100

Internal diameter tank: 2.200 mm

Distance from outlet to ground: 100 mm

Outer diameter tank: 2.400 mm

Total height of tank: 2.850 mm

Total outer width: 2.450 mm



Total outer length: 10.400 mm

Empty weight tank: 12.000

SKU: 380753

Mer information

Beskrivelse av produkt

Materiale: Syrefast 316

Modell: Horisontal

Nyprodusert/Brukt: Brukt

Arbeidstrykk i tank: trykk

Designtrekk for tanken: 10 barer

Konfiguration: isolert

Maks. arbeidstemperatur: 50 °C

Mobil tank: Nei, det er det ikke.

Omrører: Nei

Overtrykk: 4 barer

Tankens form: sylindrisk

Total uttapping: Ja

Trykktank: Ja

Oppvarming/kjøling: Nei

Væskebelastet overflate: SS AISI 316L (V4A)

Volum i liter: 35895



Utstyr

Dokument finnes: Nei
Flens for omrører: Nei
Merkeskilt: Ja
Tankutløp: innvendig Ø 100 mm
Teknisk tegning finnes: Nei, det er det ikke.
Utløpsventil: Ja

Materialoversikt

Materiale: Syrefast 316
Festepunkt(er): lakkert stål
Isolasjonsmateriale: Rockwool
Utvendig kledning: RVS 304L

Tankdimensjoner

Innvendig diameter: 2 200 mm
Mål utløp til bakken: 100 mm
Total høyde: 2 850 mm
Ytre diameter: 2 400 mm

Tanktykkelse

Bunn: 6 millimeter
Sylinder: 6 millimeter
Topp: 6 millimeter

Tykkelse på ytterbekledning og isolasjon

Finish utvendig kappe: naglet
Isolasjon bunn/gavler: Ja
Isolasjon kappe: Ja
Isolasjonsmateriale: Rockwool



Mer

Isolasjonsmateriale: Ja

Isolasjonstykkelse OW: 100

Isolert: Nei

Vekt: 12.000