3640 liters tank i syrefast 316

192 000 SEK /st exkl moms

Additional information: some residues of previous content
Volumetric volume (L): 3.640 L
Pressure in tank: pressure and vacuum
Max. pressure (Bar): 0,49 Bar

PROCESSÖVERSKOTT AB

Rodervägen 57
891 78 Bonässund
info@processoverskott.se

Läs våra köpvillkor

Min. pressure (Bar): 1 Bar

Max. temperature (°C): 2.000 °C
Material wet parts: SS AISI 316 (V4A)
Model: vertical
Configuration: insulated
Heat exchanger: no

Insulation: yes
Mobile tank: no
Total discharge: yes
Volume: 132 L
Max Overpressure: 10 Bar

Max onderdruk: 1 Bar
Max. working temperature: 200 °C
Type HE on the bottom: heating/cooling jacket
Type HE on the cylinder: heating/cooling jacket
Documents included: no

Technical drawing included: no
Registration plate on the tank: yes
Flange for agitator: no
Position of manway: headside
Outlet of tank: available

Agitator: yes
Number of revolutions: 194
Power: 5
Internal diameter tank: 1.600 mm
Cylinder height: 1.450 mm

Total height of tank: 3.500 mm
Empty weight tank: 1.600

SKU: 569045

Rodervägen 57
891 78 Bonässund
info@processoverskott.se

Mer information

Beskrivelse av produkt

Materiale: Syrefast 316
Modell: Vertikal
Nyprodusert/Brukt: Brukt
Arbeidstrykk i tank: trykk og vakuum
Konfiguration: isolert med varmeveksler
Maks. arbeidstemperatur: 2.000 °C
Mobil tank: Nei, det er det ikke.
Øvrig informasjon: Kjemi; noen rester av tidligere innhold; vi kan ikke gi noen garantier for varme-/kjølekappen; vi kan ikke gi noen garantier for røreverket
Omrører: Ja
Overtrykk: 0,49 bar
Total uttapping: Ja
Undertrykk (vakuum): 1 bar
Trykktank: Ja
Oppvarming/kjøling: Ja
Væskebelastet overflate: SS AISI 316 (V4A)
Volum i liter: 3640

Utstyr

Dokument finnes: Nei, det er det ikke.
Flens for omrører: Nei
Merkeskilt: Ja
Teknisk tegning finnes: Nei, det er det ikke.

Materialoversikt

Materiale: Syrefast 316

PROCESSÖVERSKOTT AB

Rodervägen 57
891 78 Bonässund
info@processoverskott.se

Läs våra köpvillkor

Tankdimensjoner
Sylinderhøyde: 1 450 mm
Innvendig diameter: 1 600 mm
Total høyde: 3 500 mm

Omrører
Effekt (kW): 5
Turtall: 194

Mer
Isolert: Ja
Vekt: 1.600

PROCESSÖVERSKOTT AB

Rodervägen 57
891 78 Bonässund
info@processoverskott.se

Läs våra köpvillkor