3860 liters tank i syrefast 316

259 000 SEK /st exkl moms

Additional information: Pharmaceutical chemistry; Support ring, Fe; manhole cover incomplete (see photos); bump at the insulation jacket; manhole cover plated
Volumetric volume (L): 3.860 L
Pressure in tank: pressure and vacuum
Max. pressure (Bar): 3,20 Bar

PROCESSÖVERSKOTT AB

Rodervägen 57
891 78 Bonässund
info@processoverskott.se

Läs våra köpvillkor

Min. pressure (Bar): 1 Bar

Max. temperature (°C): 200 °C
Material wet parts: SS AISI 316 (V4A)
Model: vertical
Configuration: insulated
Heat exchanger: no

Insulation: yes
Mobile tank: no
Total discharge: yes
Volume: 136 L
Max Overpressure: 16 Bar

Max onderdruk: 1 Bar
Max. working temperature: 200 °C
Type HE on the bottom: half pipe welded onto the outside of the innertank
Type HE on the cylinder: half pipe welded onto the outside of the innertank
Documents included: no

Technical drawing included: no
Registration plate on the tank: yes
Flange for agitator: no
Position of manway: headside
Outlet of tank: available

Agitator: yes
Number of revolutions: 61
Power: 4
Top: 8,14 mm
Cylinder: 6 mm

Bottom: 5,17 mm
Internal diameter tank: 1.800 mm
Outer diameter tank: 2.090 mm
Total height of tank: 3.050 mm

SKU: 406649

Rodervägen 57
891 78 Bonässund
info@processoverskott.se

Mer information

Beskrivelse av produkt

Materiale: Syrefast 316
Modell: Vertikal
Nyprodusert/Brukt: Brukt
Arbeidstrykk i tank: trykk og vakuum
Konfiguration: isolert med varmeveksler
Maks. arbeidstemperatur: 200 °C
Mobil tank: Nei, det er det ikke.
Øvrig informasjon: Farmasøytisk kjemi; Støttering, Fe; kumlokk ufullstendig (se bilder); støt ved isolasjonsmantelen; kumlokk belagt; vi kan ikke gi noen garantier om oppvarming/kjøling
Øvrig informasjon2: jakke; vi kan ikke gi noen garantier om omrøreren
Omrører: Ja
Overtrykk: 3,20 bar
Total uttapping:
Undertrykk (vakuum): 1 bar
Trykktank: Ja
Oppvarming/kjøling: Ja
Væskebelastet overflate: SS AISI 316 (V4A)
Volum i liter: 3860

Utstyr

Dokument finnes: Nei, det er det ikke.
Flens for omrører: Nei
Merkeskilt: Ja
Teknisk tegning finnes: Nei, det er det ikke.

Materialoversikt

Materiale: Syrefast 316

Rodervägen 57
891 78 Bonässund
info@processoverskott.se

Tankdimensjoner
Innvendig diameter: 1 800 mm
Total høyde: 3 050 mm
Ytre diameter: 2 090 mm

Omrører
Effekt (kW): 4
Turtall: 61

Tanktykkelse
Bunn: 5,17 mm
Sylinder: 6 millimeter
Topp: 8,14 mm

Mer
Isolert: Ja

PROCESSÖVERSKOTT AB

Rodervägen 57
891 78 Bonässund
info@processoverskott.se

Läs våra köpvillkor