# 390 liters tank i syrefast 316

186 000 SEK /st exkl moms

**Additional information**: 1 pump is included in the scope of delivery (no guarantee of functionality)
**Volumetric volume (L)**: 390 L
**Pressure in tank**: pressure and vacuum
**Max. pressure (Bar)**: 4 Bar

**PROCESSÖVERSKOTT AB**

Rodervägen 57
891 78 Bonässund
info@processoverskott.se

Läs våra köpvillkor

**Min. pressure (Bar)**: 1 Bar

**Max. temperature (°C)**: 150 °C
**Material wet parts**: SS AISI 316 (V4A)
**Model**: vertical
**Configuration**: insulated
**Heat exchanger**: no

**Insulation**: yes
**Mobile tank**: no
**Total discharge**: yes
**Volume**: 26 L
**Max Overpressure**: 6 Bar

**Max onderdruk**: 1 Bar
**Max. working temperature**: 150 °C
**Type HE on the bottom**: heating/cooling jacket
**Type HE on the cylinder**: heating/cooling jacket
**Heat exchanger**: RVS 304

**Documents included**: no
**Technical drawing included**: no
**Registration plate on the tank**: yes
**Flange for agitator**: no
**Outlet of tank**: DN40 DIN 11851

**Agitator**: yes
**Power**: 0,37
**Cylinder**: 8 mm
**Bottom**: 6 mm
**Internal diameter tank**: 650 mm

**Outer diameter tank**: 810 mm
**Cylinder height**: 990 mm
**Total height of tank**: 2.050 mm

**SKU:** 440666

**PROCESSÖVERSKOTT AB**

Rodervägen 57
891 78 Bonässund
info@processoverskott.se

Läs våra köpvillkor

# Mer information

## Beskrivelse av produkt

Materiale: Syrefast 316
Modell: Vertikal
Nyprodusert/Brukt: Brukt
Arbeidstrykk i tank: trykk og vakuum
Konfiguration: isolert med varmeveksler
Maks. arbeidstemperatur: 150 °C
Mobil tank: Nei, det er det ikke.
Øvrig informasjon: Apotek; 1 pumpe er inkludert i leveransen (ingen garanti for funksjonalitet); vi kan ikke gi noen garantier for varme- / kjølekappen; vi kan ikke gi noen garantier for omrøreren
Omrører: Ja
Overtrykk: 4 barer
Total uttapping: Ja
Undertrykk (vakuum): 1 bar
Trykktank: Ja
Oppvarming/kjøling: Ja
Væskebelastet overflate: SS AISI 316 (V4A)
Volum i liter: 390

## Utstyr

Dokument finnes: Nei, det er det ikke.
Flens for omrører: Nei
Merkeskilt: Ja
Teknisk tegning finnes: Nei, det er det ikke.

## Materialoversikt

Materiale: Syrefast 316

**PROCESSÖVERSKOTT AB**

Rodervägen 57
891 78 Bonässund
info@processoverskott.se

Läs våra köpvillkor

**Tankdimensjoner**
Sylinderhøyde: 990 mm
Innvendig diameter: 650 mm
Total høyde: 2 050 mm
Ytre diameter: 810 mm

**Omrører**
Effekt (kW): 0,37

**Tanktykkelse**
Bunn: 6 millimeter
Sylinder: 8 millimeter

**Mer**
Varmeveksler: RVS 304
Isolert: Ja

**PROCESSÖVERSKOTT AB**

Rodervägen 57
891 78 Bonässund
info@processoverskott.se

Läs våra köpvillkor