400 liters tank i syrefast 316

180 000 SEK /st exkl moms

Additional information: Pharmacy; Outlet extension slightly bent
Volumetric volume (L): 400 L
Pressure in tank: pressure and vacuum
Max. pressure (Bar): 4 Bar

PROCESSÖVERSKOTT AB

Rodervägen 57
891 78 Bonässund
info@processoverskott.se

Läs våra köpvillkor

Min. pressure (Bar): 1 Bar

Max. temperature (°C): 150 °C
Material wet parts: SS AISI 316 (V4A)
Model: vertical
Configuration: insulated with heat-exchanger
Heat exchanger: yes

Insulation: yes
Mobile tank: no
Total discharge: yes
Volume: 50 L
Max Overpressure: 6 Bar

Max onderdruk: 1 Bar
Max. working temperature: 150 °C
Type HE on the bottom: heating/cooling jacket
Type HE on the cylinder: heating/cooling jacket
Documents included: no

Technical drawing included: no
Registration plate on the tank: yes
Flange for agitator: no
Position of manway: in the bottom
Outlet of tank: 25

Agitator: yes
Number of revolutions: 1.410
Power: 1,50
Cylinder: 7,50 mm
Bottom: 5 mm

Internal diameter tank: 800 mm
Outer diameter tank: 950 mm
Cylinder height: 800 mm
Total height of tank: 2.500 mm

SKU: 408494

PROCESSÖVERSKOTT AB

Rodervägen 57
891 78 Bonässund
info@processoverskott.se

Läs våra köpvillkor

Mer information

Beskrivelse av produkt

Materiale: Syrefast 316
Modell: Vertikal
Nyprodusert/Brukt: Brukt
Arbeidstrykk i tank: trykk og vakuum
Konfiguration: isolert med varmeveksler
Maks. arbeidstemperatur: 150 °C
Mobil tank: Nei, det er det ikke.
Øvrig informasjon: Apotek; Utløpsforlengelsen er litt bøyd; vi kan ikke gi noen garantier for varme-/kjølekappen; vi kan ikke gi noen garantier for omrøreren
Omrører: Ja
Overtrykk: 4 barer
Total uttapping: Ja
Undertrykk (vakuum): 1 bar
Trykktank: Ja
Oppvarming/kjøling: Ja
Væskebelastet overflate: SS AISI 316 (V4A)
Volum i liter: 400

Utstyr

Dokument finnes: Nei
Flens for omrører: Nei
Merkeskilt: Ja
Teknisk tegning finnes: Nei, det er det ikke.

Materialoversikt

Materiale: Syrefast 316

Rodervägen 57
891 78 Bonässund
info@processoverskott.se

Tankdimensjoner

Sylinderhøyde: 800 mm
Innvendig diameter: 800 mm
Total høyde: 2 500 mm
Ytre diameter: 950 mm

Omrører

Effekt (kW): 1,50
Turtall: 1.410

Tanktykkelse

Bunn: 5 mm
Sylinder: 7,50 mm

Mer

Isolert: Ja

PROCESSÖVERSKOTT AB

Rodervägen 57
891 78 Bonässund
info@processoverskott.se

Läs våra köpvillkor