

415 liters tank i rustfritt stål 304



97 000 SEK /st exkl moms

Article type: second-hand mixing tank

Additional information: Both were never used because the startup company never started actual production. This combination is ideal for producing a wide range of liquids/liquids with powders/thickeners, such as eggnog, hair gel, pharmaceutical creams, lip gloss, polymers, adhesives, praline, sauces, mayonnaise, etc. The seal is suitable for pressure applications, for example, to empty the contents under 2 bar.; we can't give any guarantees about the agitator

Volumetric volume (L): 415 L

Ra inner weld: 0,80

Pressure in tank: pressure

Max. pressure (Bar): 0,50 Bar



Max. temperature (°C): 134 °C

Material wet parts: SS AISI 304 (V2A)

Model: vertical

Configuration: single-skin

Heat exchanger: no

Insulation: no

Mobile tank: no

Top type: dished

Shape of tank: cylindrical

Bottom type: dished

Total discharge: yes

Fixation points: 4 casters

Manway(s): RVS 304

Gasket manway(s): unknown

Suitable for food industry: yes

Documents included: no

Technical drawing included: no

Registration plate on the tank: yes

Flange for agitator: no

Number of manways: 1

Position of manway: at the top

Height manhole 1 (mm): 300 mm

Hinged lid: yes

Tank outlet: inside Ø 20 mm

Agitator: yes

Agitator type: disk agitator

Position engine: at the top

Number of revolutions: 2.935

Power: 5,50

Voltage: 380/660 V - three-phase

Current: 10.8/6.22

Distance from outlet to ground: 200 mm

Outer diameter tank: 750 mm



Cylinder height: 800 mm

Total height of tank: 2.250 mm

Total outer width: 890 mm

Total outer length: 1.050 mm

SKU: 387854

Mer information

Beskrivelse av produkt

Næringsmiddelgodkjent: Ja

Materiale: Rustfritt stål 304

Modell: Vertikal

Nyprodusert/Brukt: Brukt

Arbeidstrykk i tank: trykk

Konfiguration: enkelthudet

Maks. arbeidstemperatur: 134 °C

Mobil tank: Nei, det er det ikke.

Øvrig informasjon:

Omrører: Ja

Overtrykk: 0,50 bar

Ra innvendig sveis: 0,80

Tankens form: sylindrisk

Total uttapping:

Type bunn: tallerken

Trykktank: Ja

Oppvarming/kjøling: Nei

Væskebelastet overflate: SS AISI 304 (V2A)

Volum i liter: 415



Utstyr

Dokument finnes: Nei, det er det ikke.
Flens for omrører: Nei
Merkeskilt: Ja
Næringsmiddelgodkjent: Ja
Tankutløp: innvendig Ø 20 mm
Teknisk tegning finnes: Nei, det er det ikke.

Materialoversikt

Materiale: Rustfritt stål 304

Tankdimensjoner

Sylinderhøyde: 800 mm
Mål utløp til bakken: 200 mm
Total høyde: 2 250 mm
Ytre diameter: 750 mm

Omrører

Effekt (kW): 5,50
Motorposisjon: på toppen
Type omrører: skiveomrører
Turtall: 2.935
Spenning (Volt): 380/660 V – trefase

Mer

Isolert: Nei