

4370 liters tank i syrefast 316



103 000 SEK /st exkl moms

Article type: second-hand pressure tank

Additional information: we can't give any guarantees about the agitator

Volumetric volume (L): 4.370 L

Pressure in tank: pressure

Max. pressure (Bar): 3,20 Bar

Min. pressure (Bar): -1 Bar

Max. temperature (°C): 200 °C

Min. temperature (°C): -30 °C

Material wet parts: SS AISI 316 (V4A)

Model: vertical



Configuration: single-skin

Heat exchanger: no

Insulation: no

Mobile tank: no

Top type: dished

Shape of tank: cylindrical

Bottom type: dished

Total discharge: yes

Fixation points: 3 non adjustable feet

Fixation point(s): painted steel

Suitable for food industry: no

Documents included: no

Technical drawing included: no

Registration plate on the tank: yes

Flange for agitator: no

Number of manways: 1

Position of manway: cylinder

Height manhole 1 (mm): 500 mm

Tank outlet: inside Ø 80 mm

Total outlet valve: no

Agitator: yes

Agitator type: propeller agitator

Position engine: in the cylinder

Number of revolutions: 955

Power: 4,30

Voltage: three-phase

Top: 8 mm

Cylinder: 6 mm

Bottom: 6 mm

Distance from outlet to ground: 70 mm

Outer diameter tank: 1.780 mm

Cylinder height: 1.250 mm

Total height of tank: 2.360 mm



Empty weight tank: 1.500

SKU: 384311

Mer information

Beskrivelse av produkt

Materiale: Syrefast 316

Modell: Vertikal

Nyprodusert/Brukt: Brukt

Arbeidstrykk i tank: trykk

Konfiguration: enkelthudet

Maks. arbeidstemperatur: 200 °C

Min. arbeidstemperatur: -30 °C

Mobil tank: Nei, det er det ikke.

Øvrig informasjon: vi kan ikke gi noen garantier for omrøreren

Omrører: Ja

Overtrykk: 3,20 bar

Tankens form: sylindrisk

Total uttapping: Ja

Type bunn: tallerken

Undertrykk (vakuum): -1 bar

Trykktank: Ja

Oppvarming/kjøling: Nei

Væskebelastet overflate: SS AISI 316 (V4A)

Volum i liter: 4370



Utstyr

Dokument finnes: Nei

Flens for omrører: Nei

Merkeskilt: Ja

Tankutløp: innvendig Ø 80 mm

Teknisk tegning finnes: Nei, det er det ikke.

Utløpsventil: Nei, det er det ikke.

Materialoversikt

Materiale: Syrefast 316

Festepunkt(er): lakkert stål

Tankdimensjoner

Sylinderhøyde: 1250 mm

Mål utløp til bakken: 70 mm (2,5 tommer)

Total høyde: 2 360 mm

Ytre diameter: 1 780 mm

Omrører

Effekt (kW): 4,30

Motorposisjon: i sylinderen

Type omrører: propellomrører

Turtall: 955

Spenning (Volt): trefaset

Tanktykkelse

Bunn: 6 millimeter

Sylinder: 6 millimeter

Topp: 8 millimeter

Mer

Isolert: Nei

Vekt: 1.500

