

49338 liter tank i syrefast 316



490 000 SEK /st exkl moms

Additional information: chemistry

Volumetric volume (L): 49.338 L

Pressure in tank: pressure and vacuum

Max. pressure (Bar): 6 Bar



Min. pressure (Bar): 1 Bar

Material wet parts: SS AISI 316 (V4A)

Model: vertical

Configuration: single-skin

Heat exchanger: no

Insulation: no

Mobile tank: no

Total discharge: yes

Max Overpressure: 6 Bar

Max. working temperature: 200 °C

Type HE on the bottom: half pipe welded onto the outside of the innertank

Type HE on the cylinder: half pipe welded onto the outside of the innertank

Documents included: no

Technical drawing included: no

Registration plate on the tank: yes

Flange for agitator: no

Outlet of tank: 100

Top: 15 mm

Cylinder: 14 mm

Bottom: 18 mm

Internal diameter tank: 2.800 mm

Outer diameter tank: 3.100 mm

Cylinder height: 7.483 mm

Total height of tank: 10.000 mm

Empty weight tank: 11.600

SKU: 441554



Mer information

Beskrivelse av produkt

Materiale: Syrefast 316
Modell: Vertikal
Nyprodusert/Brukt: Brukt
Arbeidstrykk i tank: trykk og vakuum
Konfiguration: enkeltmantlet med varmeveksler
Mobil tank: Nei, det er det ikke.
Øvrig informasjon: kjemi
Omrører: Nei
Overtrykk: 6 barer
Total uttapping: Ja
Undertrykk (vakuum): 1 bar
Trykktank: Ja
Oppvarming/kjøling: Ja
Væskebelastet overflate: SS AISI 316 (V4A)
Volum i liter: 49338

Utstyr

Dokument finnes: Nei, det er det ikke.
Flens for omrører: Nei
Merkeskilt: Ja
Teknisk tegning finnes: Nei, det er det ikke.

Materialoversikt

Materiale: Syrefast 316



Tankdimensjoner

Sylinderhøyde: 7,483 mm
Innvendig diameter: 2 800 mm
Total høyde: 10 000 mm
Ytre diameter: 3 100 mm

Tanktykkelse

Bunn: 18 mm
Sylinder: 14 millimeter
Topp: 15 mm

Mer

Isolert: Nei
Vekt: 11.600