50 liters tank i syrefast 316

83 000 SEK /st exkl moms

item available on order

Article type: brand new storage tank - type VC-SLO
Volumetric volume (L): 50 L
Max. density P (kg/m³): 1.200
Ra inner weld: 0,80
Finish stainless steel: 2b

Pressure in tank: ATM - atmosferic
Max. temperature (°C): 80 °C
Min. temperature (°C): -10 °C

PROCESSÖVERSKOTT AB

Rodervägen 57
891 78 Bonässund
info@processoverskott.se

Läs våra köpvillkor

Material wet parts: SS AISI 316L (V4A)
Model: vertical

Configuration: single-skin
Heat exchanger: no
Insulation: no
Mobile tank: no
Top type: large seperat lid

Shape of tank: cylindrical
Bottom type: conical 20 °
Total discharge: yes
Fixation points: 3 non adjustable feet
Fixation point(s): RVS 304L

Suitable for food industry: yes
Documents included: yes, optional
Technical drawing included: yes
Registration plate on the tank: yes
Flange for agitator: no

CIP spray ball: no
Tank outlet: inside Ø 40 mm
Outlet type: DIN32676 clamp
Total outlet valve: no, optional
Agitator: no

Top: 2 mm
Cylinder: 2,50 mm
Bottom: 2 mm
Distance from outlet to ground: 250 mm
Outer diameter tank: 406 mm

Cylinder height: 375 mm
Total height of tank: 875 mm
Empty weight tank: 30

SKU: 377420

Rodervägen 57
891 78 Bonässund
info@processoverskott.se

Mer information

Beskrivelse av produkt

Næringsmiddelgodkjent: Ja
Materiale: Syrefast 316
Modell: Vertikal
Nyprodusert/Brukt: Nyprodusert
Arbeidstrykk i tank: ATM – atmosfærisk
Finish rustfritt stål: 2b
Konfiguration: enkelthudet
Maks. arbeidstemperatur: 80 °C
Maksimal tetthet for produktet: 1200
Min. arbeidstemperatur: -10 °C
Mobil tank: Nei, det er det ikke.
Omrører: Nei
Ra innvendig sveis: 0,80
Tankens form: sylindrisk
Total uttapping: Ja
Type bunn: konisk 20
Oppvarming/kjøling: Nei
Væskebelastet overflate: SS AISI 316L (V4A)
Volum i liter: 50

Utstyr

Flens for omrører: Nei
Merkeskilt: Ja
Næringsmiddelgodkjent: Ja
Tankutløp: innvendig Ø 40 mm
Teknisk tegning finnes: Ja
Utløpstype: DIN32676-klemme

PROCESSÖVERSKOTT AB

Rodervägen 57
891 78 Bonässund
info@processoverskott.se

Läs våra köpvillkor

Materialoversikt

Materiale: Syrefast 316
Festepunkt(er): RVS 304L

Tankdimensjoner

Sylinderhøyde: 375 mm
Mål utløp til bakken: 250 mm
Total høyde: 875 mm
Ytre diameter: 406 millimeter

Tanktykkelse

Bunn: 2 millimeter
Sylinder: 2,50 mm
Topp: 2 millimeter

Mer

Isolert: Nei
Vekt: 30

PROCESSÖVERSKOTT AB

Rodervägen 57
891 78 Bonässund
info@processoverskott.se

Läs våra köpvillkor