500 liters tank i rustfritt stål 304

36 000 SEK /st exkl moms

Additional information: Tanks placed loosely on stainless steel 304 racks (various rack designs—see photos); 1 access hole, approx. 190 x 240 mm, in the front bottom of each tank (plastic access hole cover); 1 tank with 1 dent in the cylinder
Volumetric volume (L): 500 L
Pressure in tank: pressure

PROCESSÖVERSKOTT AB

Rodervägen 57
891 78 Bonässund
info@processoverskott.se

Max. pressure (Bar): 3 Bar
Min. pressure (Bar): 3 Bar

Material wet parts: SS AISI 304 (V2A)
Model: horizontal
Configuration: single-skin
Heat exchanger: no
Insulation: no

Mobile tank: no
Total discharge: yes
Documents included: no
Technical drawing included: no
Registration plate on the tank: yes

Flange for agitator: no
Outlet of tank: 45
Internal diameter tank: 785 mm
Total outer length: 1.300 mm

SKU: 429095

Mer information

Rodervägen 57
891 78 Bonässund
info@processoverskott.se

Beskrivelse av produkt

Materiale: Rustfritt stål 304
Modell: Horisontal
Nyprodusert/Brukt: Brukt
Arbeidstrykk i tank: trykk
Konfiguration: enkelthudet
Mobil tank: Nei, det er det ikke.
Øvrig informasjon: Bryggeri; Tanker løst på rammer, Aisi 304 (forskjellige versjoner av rammene, noen skrudd sammen; se bilder); 1 håndhull hver ca. 190 x 240 mm i bunnen foran (plastdeksel for håndhull)
Øvrig informasjon2:
Omrører: Nei
Overtrykk: 3 barer
Total uttapping: Ja
Undertrykk (vakuum): 3 barer
Trykktank: Ja
Oppvarming/kjøling: Nei
Væskebelastet overflate: SS AISI 304 (V2A)
Volum i liter: 500

Utstyr

Dokument finnes: Nei, det er det ikke.
Flens for omrører: Nei
Merkeskilt: Ja
Teknisk tegning finnes: Nei, det er det ikke.

Materialoversikt

Materiale: Rustfritt stål 304

Tankdimensjoner

Innvendig diameter: 785 mm

Rodervägen 57
891 78 Bonässund
info@processoverskott.se

Mer

Isolert: Nei

PROCESSÖVERSKOTT AB

Rodervägen 57
891 78 Bonässund
info@processoverskott.se

Läs våra köpvillkor