

500 liters tank i rustfritt stål 304



58 000 SEK /st exkl moms

Article type: second-hand storage tank

Additional information: Immersion resistance DIRAC 1000W - 120°C - 230/400V; Sight glass with lighting. The tank has never been used.

Volumetric volume (L): 500 L

Pressure in tank: ATM - atmospheric

Material wet parts: SS AISI 304 (V2A)

Model: vertical

Configuration: single-skin

Heat exchanger: yes

Insulation: no



Mobile tank: no

Top type: dished

Shape of tank: cylindrical

Bottom type: flat sloping

Wall type: flat

Bottom outlet: yes

Total discharge: yes

Fixation points: 4 stackable frame

Manway(s): RVS 304

Valve: RVS 304

Fixation point(s): galvanised steel

Suitable for food industry: no

Documents included: no

Technical drawing included: yes

Registration plate on the tank: no

Flange for agitator: no

Number of manways: 1

Position of manway: at the top

Outlet of tank: DN50

Total outlet valve: yes

Outer diameter tank: 1.080 mm

Cylinder height: 500 mm

Height of top: 1.041 mm

Total height of tank: 1.041 mm

Total outer width: 1.121 mm

SKU: 425342



Mer information

Beskrivelse av produkt

Materiale: Rustfritt stål 304

Modell: Vertikal

Nyprodusert/Brukt: Brukt

Arbeidstrykk i tank: ATM – atmosfærisk

Konfiguration: enkelthudet

Mobil tank: Nei, det er det ikke.

Øvrig informasjon: Nedsenkingsmotstand DIRAC 1000W – 120°C – 230/400V; Skueglass med belysning. Tanken har aldri vært i bruk.

Omrører: Nei

Tankens form: sylindrisk

Total uttapping: Ja

Type bunn: flat skråning

Oppvarming/kjøling: Ja

Væskebelastet overflate: SS AISI 304 (V2A)

Volum i liter: 500

Utstyr

Dokument finnes: Nei, det er det ikke.

Flens for omrører: Nei

Merkeskilt: Nei, det er det ikke.

Teknisk tegning finnes: Ja

Utløpsventil: Ja

Materialoversikt

Materiale: Rustfritt stål 304

Festepunkt(er): galvanisert stål



Tankdimensjoner

Sylinderhøyde: 500 mm

Total høyde: 1,041 mm

Ytre diameter: 1 080 mm

Mer

Isolert: Nei