

500 liters tank i syrefast 316



93 000 SEK /st exkl moms

Additional information: An inner double jacket was subsequently welded into the vessel by the previous operator, which reduced the volume indicated on the type plate to approx. 500 liters (see photos); unfortunately, we do not know to what extent the pressure and temperature specifications on the type plate are still valid as a result; total inner diameter of the tank approx. 900 mm, in the area of the inner double jacket approx. 760 mm; 1 hand hole diameter 150 mm in the upper bottom; outlet fitting no longer present;



pipe end cut flush

Volumetric volume (L): 500 L

Pressure in tank: ATM - atmosferic

Material wet parts: SS AISI 316 (V4A)

Model: vertical

Configuration: insulated

Heat exchanger: no

Insulation: yes

Mobile tank: no

Total discharge: yes

Type HE on the cylinder: heating/cooling jacket

Documents included: no

Technical drawing included: no

Registration plate on the tank: yes

Flange for agitator: no

Outlet of tank: 42

Agitator: yes

Number of revolutions: 50 - 480

Outer diameter tank: 1.000 mm

Total height of tank: 2.300 mm

SKU: 404579

Mer information



Beskrivelse av produkt

Materiale: Syrefast 316
Modell: Vertikal
Nyprodusert/Brukt: Brukt
Arbeidstrykk i tank: ATM – atmosfærisk
Konfiguration: isolert med varmeveksler
Mobil tank: Nei, det er det ikke.
Øvrig informasjon:
Øvrig informasjon2:
Omrører: Ja
Total uttapping: Ja
Oppvarming/kjøling: Ja
Væskebelastet overflate: SS AISI 316 (V4A)
Volum i liter: 500

Utstyr

Dokument finnes: Nei, det er det ikke.
Flens for omrører: Nei
Merkeskilt: Ja
Teknisk tegning finnes: Nei, det er det ikke.

Materialoversikt

Materiale: Syrefast 316

Tankdimensjoner

Total høyde: 2 300 mm
Ytre diameter: 1.000 mm

Omrører

Turtall: 50 – 480

Mer

Isolert: Ja

