500 liters tank i syrefast 316

43 000 SEK /st exkl moms

Additional information: Spout with bead and 2 connections Diameter inside approx. 60 mm; 3 plastic base plates; slight metallic discoloration inside
Volumetric volume (L): 500 L
Pressure in tank: ATM - atmosferic
Material wet parts: SS AISI 316 (V4A)

PROCESSÖVERSKOTT AB

Rodervägen 57
891 78 Bonässund
info@processoverskott.se

Läs våra köpvillkor

Model: vertical

Configuration: single-skin
Heat exchanger: no
Insulation: no
Mobile tank: no
Total discharge: yes

Documents included: no
Technical drawing included: no
Registration plate on the tank: yes
Flange for agitator: no
Position of manway: in the bottom

Outlet of tank: available
Agitator: yes
Number of revolutions: 59
Power: 0,25
Cylinder: 3 mm

Internal diameter tank: 930 mm
Cylinder height: 970 mm
Total height of tank: 2.200 mm

SKU: 486926

Mer information

PROCESSÖVERSKOTT AB

Rodervägen 57
891 78 Bonässund
info@processoverskott.se

Läs våra köpvillkor

Beskrivelse av produkt

Materiale: Syrefast 316
Modell: Vertikal
Nyprodusert/Brukt: Brukt
Arbeidstrykk i tank: ATM – atmosfærisk
Konfiguration: enkelthudet
Mobil tank: Nei, det er det ikke.
Øvrig informasjon: Meieri; Utløp med perle og 2 tilkoblinger, indre diameter ca. 60 mm; 3 bunnplater av plast; lett metallisk misfarging innvendig; vi kan ikke gi noen garantier for omrøreren
Omrører: Ja
Total uttapping: Ja
Oppvarming/kjøling: Nei
Væskebelastet overflate: SS AISI 316 (V4A)
Volum i liter: 500

Utstyr

Dokument finnes: Nei, det er det ikke.
Flens for omrører: Nei
Merkeskilt: Ja
Teknisk tegning finnes: Nei, det er det ikke.

Materialoversikt

Materiale: Syrefast 316

Tankdimensjoner

Sylinderhøyde: 970 mm
Innvendig diameter: 930 mm
Total høyde: 2 200 mm

Omrører

Effekt (kW): 0,25
Turtall: 59

PROCESSÖVERSKOTT AB

Rodervägen 57
891 78 Bonässund
info@processoverskott.se

Läs våra köpvillkor

Tanktykkelse
Sylinder: 3 mm

Mer
Isolert: Nei

PROCESSÖVERSKOTT AB

Rodervägen 57
891 78 Bonässund
info@processoverskott.se

Läs våra köpvillkor