

500 liters tank i syrefast 316





59 000 SEK /st exkl moms

Article type: brand new storage tank - type K-SL

Volumetric volume (L): 500 L

Max. density P (kg/m³): 1.200

Ra inner weld: 1,60

Finish stainless steel: 2b

Pressure in tank: ATM - atmospheric

Material wet parts: SS AISI 316 (V4A)

Model: vertical

Configuration: single-skin

Heat exchanger: no

Insulation: no

Mobile tank: no

Top type: conical 15 %

Shape of tank: cylindrical

Bottom type: conical 15 %

Total discharge: yes

Fixation points: 3 adjustable feet

Legs: Set of baseplates and adjusting pieces included

Manway(s): RVS 316

Valve: RVS 316L

Fixation point(s): RVS 304

Suitable for food industry: yes

Documents included: yes, optional

Technical drawing included: yes

Registration plate on the tank: yes

Flange for agitator: no

Number of manways: 1

Position of manway: at the top

Height manhole 1 (mm): 400 mm

Hinged lid: yes

CIP spray ball: no

Tank outlet: inside Ø 50 mm

Outlet type: DIN11851

Total outlet valve: no, optional

Adjustable legs: yes

Agitator: no, optional

Top: 2,50 mm

Cylinder: 2 mm

Bottom: 2,50 mm

Distance from outlet to ground: 240 mm

Outer diameter tank: 796 mm

Cylinder height: 1.000 mm

Total height of tank: 1.635 mm

Empty weight tank: 80

SKU: 375992

Mer information



Beskrivelse av produkt

Næringsmiddelgodkjent: Ja
Materiale: Syrefast 316
Modell: Vertikal
Nyprodusert/Brukt: Nyprodusert
Arbeidstrykk i tank:
Finish rustfritt stål: 2b
Konfiguration: enkelthudet
Maksimal tetthet for produktet: 1200
Mobil tank: Nei, det er det ikke.
Omrører: Nei
Ra innvendig sveis: 1,60
Tankens form: sylindrisk
Total uttapping:
Type bunn: konisk 15
Oppvarming/kjøling: Nei
Væskebelastet overflate: SS AISI 316 (V4A)
Volum i liter: 500

Utstyr

Flens for omrører: Nei
Merkeskilt: Ja
Næringsmiddelgodkjent: Ja
Tankutløp: innvendig Ø 50 mm
Teknisk tegning finnes: Ja
Utløpstype: DIN11851

Materialoversikt

Materiale: Syrefast 316
Festepunkt(er): RVS 304



Tankdimensjoner

Sylinderhøyde: 1 000 mm
Mål utløp til bakken: 240 mm
Total høyde: 1 635 mm
Ytre diameter: 796 mm

Tanktykkelse

Bunn: 2,50 mm
Sylinder: 2 millimeter
Topp: 2,50 mm

Mer

Isolert: Nei
Vekt: 80