

500 liters tank i syrefast 316



345 000 SEK /st exkl moms

Additional information: Full set of pharma-compliant technical documentation included in delivery; tank was manufactured for a global pharmaceutical company but was never put into operation; hand hole with sight glass diameter: 285mm

Volumetric volume (L): 500 L

Pressure in tank: pressure and vacuum



Max. pressure (Bar): 6 Bar

Min. pressure (Bar): 1 Bar

Max. temperature (°C): 150 °C

Material wet parts: SS AISI 316 (V4A)

Model: vertical

Configuration: insulated with heat-exchanger

Heat exchanger: yes

Insulation: yes

Mobile tank: no

Total discharge: yes

Volume: 88 L

Max Overpressure: 10 Bar

Max onderdruk: 1 Bar

Max. working temperature: 150 °C

Type HE on the cylinder: half pipe welded onto the outside of the innertank

Documents included: no

Technical drawing included: no

Registration plate on the tank: yes

Flange for agitator: no

Outlet of tank: available

Agitator: yes

Number of revolutions: 408

Power: 0,37

Top: 4,30 mm

Cylinder: 8,90 mm

Bottom: 6,10 mm

Internal diameter tank: 780 mm

Outer diameter tank: 960 mm

Cylinder height: 1.015 mm

Empty weight tank: 1.000

SKU: 441269



Mer information

Beskrivelse av produkt

Materiale: Syrefast 316

Modell: Vertikal

Nyprodusert/Brukt: Brukt

Arbeidstrykk i tank: trykk og vakuum

Konfiguration: isolert med varmeveksler

Maks. arbeidstemperatur: 150 °C

Mobil tank: Nei, det er det ikke.

Øvrig informasjon:

Øvrig informasjon2: diameter: 285 mm; vi kan ikke gi noen garantier for varme-/kjølekappen; vi kan ikke gi noen garantier for omrøreren

Omrører: Ja

Overtrykk: 6 barer

Total uttapping: Ja

Undertrykk (vakuum): 1 bar

Trykktank: Ja

Oppvarming/kjøling: Ja

Væskebelastet overflate: SS AISI 316 (V4A)

Volum i liter: 500

Utstyr

Dokument finnes: Nei, det er det ikke.

Flens for omrører: Nei

Merkeskilt: Ja

Teknisk tegning finnes: Nei, det er det ikke.

Materialoversikt

Materiale: Syrefast 316



Tankdimensjoner

Sylinderhøyde: 1,015 mm
Innvendig diameter: 780 mm
Ytre diameter: 960 mm

Omrører

Effekt (kW): 0,37
Turtall: 408

Tanktykkelse

Bunn: 6,10 mm
Sylinder: 8,90 mm
Topp: 4,30 mm

Mer

Isolert: Ja
Vekt: 1.000