# 5000 liters tank i rustfritt stål 304

121 000 SEK /st exkl moms

**Article type**: second-hand mixing tank
**Additional information**: we can't give any guarantees about the heating/cooling jacket; we can't give any guarantees about the agitator
**Volumetric volume (L)**: 5.000 L
**Pressure in tank**: ATM - atmosferic
**Material wet parts**: SS AISI 304 (V2A)

**Model**: vertical
**Configuration**: insulated with heat-exchanger
**Heat exchanger**: yes
**Insulation**: yes

**PROCESSÖVERSKOTT AB**

Rodervägen 57
891 78 Bonässund
info@processoverskott.se

Läs våra köpvillkor

**Mobile tank**: no

**Top type**: conical
**Shape of tank**: cylindrical
**Bottom type**: conical
**Bottom outlet**: yes
**Total discharge**: yes

**Fixation points**: 3 adjustable feet
**Type of HE on the cylinder**: half pipe welded onto the outside of the innertank
**Position HE**: the complet cilinder
**Type of HE on the bottom**: half pipe welded onto the outside of the innertank
**Manway(s)**: RVS 304

**Gasket manway(s)**: unknown
**Fixation point(s)**: RVS 304
**Suitable for food industry**: yes
**Documents included**: no
**Technical drawing included**: no

**Registration plate on the tank**: no
**Flange for agitator**: no
**Number of manways**: 1
**Position of manway**: at the top
**Hinged lid**: yes

**Tank outlet**: inside Ø 60 mm
**Agitator**: yes
**Agitator type**: propeller agitator
**Power**: 1,20
**Voltage**: 400 V - three-phase

**Current**: 3,10
**Distance from outlet to ground**: 600 mm
**Outer diameter tank**: 2.000 mm
**Cylinder height**: 2.245 mm
**Total height of tank**: 3.800 mm

**Empty weight tank**: 1.050

**PROCESSÖVERSKOTT AB**

Rodervägen 57
891 78 Bonässund
info@processoverskott.se

Läs våra köpvillkor

**SKU:** 416963

## Mer information

### Beskrivelse av produkt

Næringsmiddelgodkjent: Ja
Materiale: Rustfritt stål 304
Modell: Vertikal
Nyprodusert/Brukt: Brukt
Arbeidstrykk i tank:
Konfiguration: isolert med varmeveksler
Mobil tank: Nei, det er det ikke.
Øvrig informasjon: vi kan ikke gi noen garantier for varme-/kjølekappen; vi kan ikke gi noen garantier for omrøreren
Omrører: Ja
Tankens form: sylindrisk
Total uttapping:
Type bunn: konisk
Oppvarming/kjøling: Ja
Væskebelastet overflate: SS AISI 304 (V2A)
Volum i liter: 5000

### Utstyr

Dokument finnes: Nei, det er det ikke.
Flens for omrører: Nei
Merkeskilt: Nei, det er det ikke.
Næringsmiddelgodkjent: Ja
Tankutløp: innvendig Ø 60 mm
Teknisk tegning finnes: Nei, det er det ikke.



Rodervägen 57
891 78 Bonässund
info@processoverskott.se

**Materialoversikt**

Materiale: Rustfritt stål 304
Festepunkt(er): RVS 304

**Tankdimensjoner**

Sylinderhøyde: 2,245 mm
Mål utløp til bakken: 600 mm
Total høyde: 3 800 mm
Ytre diameter: 2 000 mm

**Varmevekslere**

Posisjon varmeveksler: den komplette sylinderen
Type varmeveksler på sylinder: halvrør sveiset på utsiden av innertanken
Type varmeveksler på bunn: halvrør sveiset på utsiden av innertanken

**Omrører**

Effekt (kW): 1,20
Type omrører: propellomrører
Spenning (Volt): 400 V – trefase

**Mer**

Isolert: Ja
Vekt: 1.050

**PROCESSÖVERSKOTT AB**

Rodervägen 57
891 78 Bonässund
info@processoverskott.se

Läs våra köpvillkor