

5000 liters tank i syrefast 316



107 000 SEK /st exkl moms

Additional information: Food industry; 1 dent in the inner tank (overpressure of the no longer functional heating jacket; see photos); insulation jacket with smaller dents and partially detached plates; tank with adhesions inside; Devices for load cells under the feet (3 loose load cells are included in the scope of delivery; these were not taken into account when specifying the total height)

Volumetric volume (L): 5.000 L



Pressure in tank: ATM - atmosferic
Material wet parts: SS AISI 316 (V4A)
Model: vertical

Configuration: insulated
Heat exchanger: no
Insulation: yes
Mobile tank: no
Total discharge: yes

Documents included: no
Technical drawing included: no
Registration plate on the tank: no
Flange for agitator: no
Position of manway: headside

Outlet of tank: 48
Agitator: yes
Number of revolutions: 450 / 965
Power: 1.1 / 4.4
Internal diameter tank: 1.790 mm

Outer diameter tank: 1.900 mm
Cylinder height: 2.100 mm
Total height of tank: 4.150 mm

SKU: 446723

Mer information



Beskrivelse av produkt

Materiale: Syrefast 316
Modell: Vertikal
Nyprodusert/Brukt: Brukt
Arbeidstrykk i tank: ATM – atmosfærisk
Konfiguration: isolert
Mobil tank: Nei, det er det ikke.
Øvrig informasjon:
Øvrig informasjon2:
Omrører: Ja
Total uttapping: Ja
Oppvarming/kjøling: Nei
Væskebelastet overflate: SS AISI 316 (V4A)
Volum i liter: 5000

Utstyr

Dokument finnes: Nei, det er det ikke.
Flens for omrører: Nei
Merkeskilt: Nei, det er det ikke.
Teknisk tegning finnes: Nei, det er det ikke.

Materialoversikt

Materiale: Syrefast 316

Tankdimensjoner

Sylinderhøyde: 2100 mm
Innvendig diameter: 1790 mm
Total høyde: 4 150 mm
Ytre diameter: 1 900 mm

Omrører

Effekt (kW): 1.1 / 4.4
Turtall: 450 / 965



Mer

Isolert: Ja