50000 liters tank i rustfritt stål 304

353 000 SEK /st exkl moms

Article type: second-hand mixing tank
Additional information: we can't give any guarantees about the agitator
Volumetric volume (L): 50.000 L
Pressure in tank: ATM - atmosferic
Material wet parts: SS AISI 304 (V2A)

Model: vertical
Configuration: insulated
Heat exchanger: no
Insulation: yes
Mobile tank: no

PROCESSÖVERSKOTT AB

Rodervägen 57
891 78 Bonässund
info@processoverskott.se

Läs våra köpvillkor

Top type: conical
Shape of tank: cylindrical
Bottom type: conical
Total discharge: yes
Fixation points: 3 non adjustable feet

Insulation material: Rockwool
Outer jacket (ornamental wall): RVS 304
Spray ball: RVS 304
Manway(s): RVS 304
Gasket manway(s): unknown

Fixation point(s): RVS 304
Suitable for food industry: yes
Documents included: no
Technical drawing included: no
Registration plate on the tank: no

Flange for agitator: no
Number of manways: 2
Position of manway: headside
Height manhole 1 (mm): 430 mm
Position 2nd manway: cylinder

Tank outlet: inside Ø 65 mm
Total outlet valve: no
Agitator: yes
Agitator type: tripad
Position engine: at the top

Power: 7,50
Voltage: three-phase
Distance from outlet to ground: 600 mm
Outer diameter tank: 3.000 mm
Cylinder height: 8.200 mm

Total height of tank: 10.700 mm
Empty weight tank: 5.000

PROCESSÖVERSKOTT AB

Rodervägen 57
891 78 Bonässund
info@processoverskott.se

Läs våra köpvillkor

SKU: 382253

Mer information

Beskrivelse av produkt

Næringsmiddelgodkjent: Ja
Materiale: Rustfritt stål 304
Modell: Vertikal
Nyprodusert/Brukt: Brukt
Arbeidstrykk i tank: ATM – atmosfærisk
Konfiguration: isolert
Mobil tank: Nei, det er det ikke.
Øvrig informasjon: vi kan ikke gi noen garantier for omrøreren
Omrører: Ja
Tankens form: sylindrisk
Total uttapping: Ja
Type bunn: konisk
Oppvarming/kjøling: Nei
Væskebelastet overflate: SS AISI 304 (V2A)
Volum i liter: 50000

Utstyr

Dokument finnes: Nei
Flens for omrører: Nei
Merkeskilt: Nei, det er det ikke.
Næringsmiddelgodkjent: Ja
Tankutløp: innvendig Ø 65 mm
Teknisk tegning finnes: Nei, det er det ikke.
Utløpsventil: Nei, det er det ikke.

PROCESSÖVERSKOTT AB

Rodervägen 57
891 78 Bonässund
info@processoverskott.se

Läs våra köpvillkor

Materialoversikt

Materiale: Rustfritt stål 304
Festepunkt(er): RVS 304
Isolasjonsmateriale: Rockwool
Utvendig kledning: RVS 304

Tankdimensjoner

Sylinderhøyde: 8 200 mm
Mål utløp til bakken: 600 mm
Total høyde: 10 700 mm
Ytre diameter: 3 000 mm

Omrører

Effekt (kW): 7,50
Motorposisjon: på toppen
Type omrører: tripad
Spenning (Volt): trefaset

Tykkelse på ytterbekledning og isolasjon

Isolasjonsmateriale: Rockwool

Mer

Isolert: Ja
Vekt: 5.000

Rodervägen 57
891 78 Bonässund
info@processoverskott.se