

50000 liters tank i syrefast 316



465 000 SEK /st exkl moms

item available on order

Article type: brand new storage tank - type TZN-SL

Volumetric volume (L): 50.000 L

Max. density P (kg/m³): 1.000

Pressure in tank: ATM - atmospheric

Max. temperature (°C): 40 °C

Material wet parts: SS AISI 316 (V4A)

Model: vertical

Configuration: single-skin



Heat exchanger: no

Insulation: no

Mobile tank: no

Top type: conical 15 °

Shape of tank: cylindrical

Bottom type: conical 20 °

Total discharge: yes

Fixation points: 6 non adjustable feet

Manway(s): RVS 316

Gasket manway(s): EPDM

Valve: RVS 316L

Fixation point(s): RVS 304

Suitable for food industry: yes

Documents included: no

Technical drawing included: no

Registration plate on the tank: no

Flange for agitator: no

Number of manways: 2

Position of manway: headside

Height manhole 1 (mm): 500 mm

Hinged lid: yes

Position 2nd manway: cylinder

Height manhole 2 (mm): 440 x 308 mm

Hinged lid: yes

CIP spray ball: no

Tank outlet: inside Ø 80 mm

Outlet type: DIN 11850

Total outlet valve: no, optional

Agitator: no

Top: 3 mm

Cylinder: 2,50 mm

Bottom: 4 mm

Distance from outlet to ground: 405 mm



Outer diameter tank: 3.000 mm

Cylinder height: 7.000 mm

Height of top: 443 mm

Height of bottom: 615 mm

Feet height: 945 mm

Total height of tank: 8.800 mm

Empty weight tank: 1.850

SKU: 374867

Mer information

Beskrivelse av produkt

Næringsmiddelgodkjent: Ja

Materiale: Syrefast 316

Modell: Vertikal

Nyprodusert/Brukt: Nyprodusert

Arbeidstrykk i tank: ATM – atmosfærisk

Konfiguration: enkelthudet

Maks. arbeidstemperatur: 40 °C

Maksimal tetthet for produktet: 1000

Mobil tank: Nei, det er det ikke.

Omrører: Nei

Tankens form: sylindrisk

Total uttapping: Ja

Type bunn: konisk 20

Oppvarming/kjøling: Nei

Væskebelastet overflate: SS AISI 316 (V4A)

Volum i liter: 50000



Utstyr

Dokument finnes: Nei
Flens for omrører: Nei
Merkeskilt: Nei, det er det ikke.
Næringsmiddelgodkjent: Ja
Tankutløp: innvendig Ø 80 mm
Teknisk tegning finnes: Nei, det er det ikke.
Utløpstype: DIN 11850

Materialoversikt

Materiale: Syrefast 316
Festepunkt(er): RVS 304

Tankdimensjoner

Sylinderhøyde: 7 000 mm
Høyde på ben: 945 millimeter
Mål utløp til bakken: 405 millimeter
Total høyde: 8 800 mm
Ytre diameter: 3 000 mm

Tanktykkelse

Bunn: 4 mm
Sylinder: 2,50 mm
Topp: 3 mm

Mer

Isolert: Nei
Vekt: 1.850