

5236 liters tank i syrefast 316



157 000 SEK /st exkl moms

Volumetric volume (L): 5.236 L

Pressure in tank: pressure

Max. temperature (°C): 120 °C

Material wet parts: SS AISI 304 (V2A)



Model: vertical

Configuration: single-skin

Heat exchanger: no

Insulation: no

Mobile tank: no

Total discharge: yes

Volume: 22 L

Max Overpressure: 3 Bar

Max. working temperature: 120 °C

Heat exchanger: RVS 304

Documents included: no

Technical drawing included: no

Registration plate on the tank: yes

Flange for agitator: yes

Position of manway: headside

Outlet of tank: DN50 DIN 11851

Top: 2,50 mm

Cylinder: 3 mm

Bottom: 3 mm

Internal diameter tank: 1.990 mm

Cylinder height: 1.500 mm

Total height of tank: 2.770 mm

SKU: 419321



Mer information

Beskrivelse av produkt

Materiale: Rustfritt stål 304

Modell: Vertikal

Nyprodusert/Brukt: Brukt

Arbeidstrykk i tank: ATM – atmosfærisk

Konfiguration: enkeltmantlet med varmeveksler

Maks. arbeidstemperatur: 120 °C

Mobil tank: Nei, det er det ikke.

Omrører: Nei

Total uttapping: Ja

Oppvarming/kjøling: Ja

Væskebelastet overflate: SS AISI 304 (V2A)

Volum i liter: 5236

Utstyr

Dokument finnes: Nei, det er det ikke.

Flens for omrører: Ja

Merkeskilt: Ja

Teknisk tegning finnes: Nei, det er det ikke.

Materialoversikt

Materiale: Rustfritt stål 304

Tankdimensjoner

Sylinderhøyde: 1 500 mm

Innvendig diameter: 1 990 mm

Total høyde: 2770 mm

Tanktykkelse

Bunn: 3 mm

Sylinder: 3 mm

Topp: 2,50 mm



Mer

Varmeveksler: RVS 304

Isolert: Nei