# 530 liters tank i syrefast 316

171 000 SEK /st exkl moms

**Additional information**: Double jacket must be operated without pressure; 2 electric heaters (6 kW) for heating the heating medium in the double jacket; Attention: The vessel is delivered without heating medium (glycerine or thermal oil), which must be filled in on site before commissioning; switch cabinet for the electric heaters available (temperature of the double jacket can be regulated via switch cabinet); 2 ball valves for the heating jacket are included in the scope of delivery.

**PROCESSÖVERSKOTT AB**

Rodervägen 57
891 78 Bonässund
info@processoverskott.se

Läs våra köpvillkor

**Volumetric volume (L)**: 530 L
**Pressure in tank**: ATM - atmosferic
**Max. temperature (°C)**: 90 °C
**Material wet parts**: SS AISI 316 (V4A)

**Model**: vertical
**Configuration**: insulated
**Heat exchanger**: no
**Insulation**: yes
**Mobile tank**: no

**Total discharge**: yes
**Type HE on the bottom**: heating/cooling jacket
**Type HE on the cylinder**: heating/cooling jacket
**Documents included**: no
**Technical drawing included**: no

**Registration plate on the tank**: yes
**Flange for agitator**: no
**Outlet of tank**: DN50 DIN 11851
**Agitator**: yes
**Number of revolutions**: 0 - 1400

**Power**: 0,75
**Cylinder**: 2 mm
**Bottom**: 2 mm
**Internal diameter tank**: 945 mm
**Outer diameter tank**: 1.050 mm

**Cylinder height**: 750 mm
**Total height of tank**: 1.650 mm

**SKU:** 415253

**PROCESSÖVERSKOTT AB**

Rodervägen 57
891 78 Bonässund
info@processoverskott.se

Läs våra köpvillkor

# Mer information

## Beskrivelse av produkt

Materiale: Syrefast 316
Modell: Vertikal
Nyprodusert/Brukt: Brukt
Arbeidstrykk i tank: ATM – atmosfærisk
Konfiguration: isolert med varmeveksler
Maks. arbeidstemperatur: 90 °C
Mobil tank: Nei, det er det ikke.
Øvrig informasjon: Dobbeltmantelen må drives uten trykk; 2 elektriske varmeovner (6 kW) for oppvarming av varmemediet i dobbeltmantelen; OBS: Tanken leveres uten varmemedium (glyserin)
Øvrig informasjon2:
Omrører: Ja
Total uttapping: Ja
Oppvarming/kjøling: Ja
Væskebelastet overflate: SS AISI 316 (V4A)
Volum i liter: 530

## Utstyr

Dokument finnes: Nei, det er det ikke.
Flens for omrører: Nei
Merkeskilt: Ja
Teknisk tegning finnes: Nei, det er det ikke.

## Materialoversikt

Materiale: Syrefast 316



Rodervägen 57
891 78 Bonässund
info@processoverskott.se

**Tankdimensjoner**

Sylinderhøyde: 750 mm
Innvendig diameter: 945 millimeter
Total høyde: 1 650 mm
Ytre diameter: 1 050 mm

**Omrører**

Effekt (kW): 0,75
Turtall: 0 – 1400

**Tanktykkelse**

Bunn: 2 millimeter
Sylinder: 2 millimeter

**Mer**

Isolert: Ja

**PROCESSÖVERSKOTT AB**

Rodervägen 57
891 78 Bonässund
info@processoverskott.se

Läs våra köpvillkor