

5300 liters tank i rustfritt stål 304



107 000 SEK /st exkl moms

item available on order

Article type: brand new storage tank - type K-HL

Volumetric volume (L): 5.300 L

Max. density P (kg/m³): 1.150

Pressure in tank: pressure

Max. temperature (°C): 100 °C

Material wet parts: SS AISI 304 (V2A)

Model: vertical

Configuration: single jacketed with heat-exchanger



Heat exchanger: yes

Insulation: no

Mobile tank: no

Top type: conical 18 °

Shape of tank: cylindrical

Bottom type: conical 18 °

Total discharge: yes

Fixation points: 4 adjustable feet

Legs: Set of baseplates and adjusting pieces included

Type of HE on the cylinder: half pipe welded onto the outside of the innertank

Position HE: the middle part of the cylinder

Number of windings: 5

Height HE: 1.061 mm

Number of sections: 1

Water pressure HE: 2,50 Bar

Steam pressure HE: 2,50 Bar

Contact surface cylinder: 3 m²

Type HE: half pipe welded onto the outside of the innertank

Heat exchanger: RVS 304

Manway(s): RVS 304

Gasket manway(s): parra rubber

Valve: RVS 316L

Fixation point(s): RVS 304

Suitable for food industry: yes

Documents included: yes, optional

Technical drawing included: yes

Registration plate on the tank: yes

Flange for agitator: no

Number of manways: 1

Position of manway: at the top

Height manhole 1 (mm): 500 mm

Hinged lid: yes

CIP spray ball: no

Tank outlet: inside Ø 65 mm

Outlet type: DIN11851 male

Total outlet valve: no, optional

Adjustable legs: yes

Agitator: no, optional

Top: 1,50 mm

Cylinder: 2 mm

Bottom: 2 mm

Internal diameter tank: 1.592 mm

Distance from outlet to ground: 230 mm

Outer diameter tank: 1.622 mm

Cylinder height: 2.500 mm

Feet height: 570 mm

Total height of tank: 3.500 mm

Empty weight tank: 350

SKU: 374825

Mer information



Beskrivelse av produkt

Næringsmiddelgodkjent: Ja
Materiale: Rustfritt stål 304
Modell: Vertikal
Nyprodusert/Brukt: Nyprodusert
Arbeidstrykk i tank: trykk
Konfiguration: enkeltmantlet med varmeveksler
Maks. arbeidstemperatur: 100 °C
Maksimal tetthet for produktet: 1150
Mobil tank: Nei, det er det ikke.
Omrører: Nei
Tankens form: sylindrisk
Total uttapping:
Type bunn: konisk 18°.
Oppvarming/kjøling: Ja
Væskebelastet overflate: SS AISI 304 (V2A)
Volum i liter: 5300

Utstyr

Flens for omrører: Nei
Merkeskilt: Ja
Næringsmiddelgodkjent: Ja
Tankutløp: innvendig Ø 65 mm
Teknisk tegning finnes: Ja
Utløpstype: DIN11851 hann

Materialoversikt

Materiale: Rustfritt stål 304
Festepunkt(er): RVS 304



Tankdimensjoner

Sylinderhøyde: 2 500 mm
Høyde på ben: 570 mm
Innvendig diameter: 1592 mm
Mål utløp til bakken: 230 mm
Total høyde: 3 500 mm
Ytre diameter: 1622 mm

Varmevekslere

Damptrykk varmeveksler: 2,50 Bar
Høyde varmeveksler: 1,061 mm
Kontaktflate sylinder: 3 m²
Posisjon varmeveksler: den midtre delen av cilinderen
Type varmeveksler på sylinder: halvrør sveiset på utsiden av innertanken
Vanntrykk varmeveksler: 2,50 bar

Tanktykkelse

Bunn: 2 millimeter
Sylinder: 2 millimeter
Topp: 1,50 mm

Mer

Varmeveksler: RVS 304
Isolert: Nei
Vekt: 350