

532 liters tank i syrefast 316



226 000 SEK /st exkl moms

Additional information: Fully comprehensive documentation in accordance with pharmaceutical industry standards included in the scope of delivery; device was manufactured for a global pharmaceutical company but never put into operation there; hand hole with sight glass diameter: 100 mm; incl. Südmo single seat valve SVP (outlet)

Volumetric volume (L): 532 L



Pressure in tank: pressure and vacuum

Max. pressure (Bar): 6 Bar

Min. pressure (Bar): 1 Bar

Max. temperature (°C): 150 °C

Material wet parts: SS AISI 316 (V4A)

Model: vertical

Configuration: insulated

Heat exchanger: no

Insulation: yes

Mobile tank: no

Total discharge: yes

Volume: 24 L

Max Overpressure: 10 Bar

Max onderdruk: 1 Bar

Max. working temperature: 150 °C

Type HE on the cylinder: half pipe welded onto the outside of the innertank

Documents included: no

Technical drawing included: no

Registration plate on the tank: yes

Flange for agitator: no

Outlet of tank: available

Top: 8 mm

Cylinder: 5 mm

Bottom: 6 mm

Internal diameter tank: 800 mm

Outer diameter tank: 1.000 mm

Cylinder height: 1.040 mm

Total height of tank: 1.981 mm

Empty weight tank: 800

SKU: 440900



Mer information

Beskrivelse av produkt

Materiale: Syrefast 316

Modell: Vertikal

Nyprodusert/Brukt: Brukt

Arbeidstrykk i tank: trykk og vakuum

Konfiguration: isolert med varmeveksler

Maks. arbeidstemperatur: 150 °C

Mobil tank: Nei, det er det ikke.

Øvrig informasjon:

Øvrig informasjon2: diameter: 100 mm; inkl. Súdmo enkeltseteventil SVP (utløp); vi kan ikke gi noen garantier for varme-/kjølekappen

Omrører: Nei

Overtrykk: 6 barer

Total uttapping: Ja

Undertrykk (vakuum): 1 bar

Trykktank: Ja

Oppvarming/kjøling: Ja

Væskebelastet overflate: SS AISI 316 (V4A)

Volum i liter: 532

Utstyr

Dokument finnes: Nei

Flens for omrører: Nei

Merkeskilt: Ja

Teknisk tegning finnes: Nei, det er det ikke.

Materialoversikt

Materiale: Syrefast 316



Tankdimensjoner

Sylinderhøyde: 1 040 mm
Innvendig diameter: 800 mm
Total høyde: 1,981 mm
Ytre diameter: 1.000 mm

Tanktykkelse

Bunn: 6 millimeter
Sylinder: 5 mm
Topp: 8 millimeter

Mer

Isolert: Ja
Vekt: 800