

5380 liter tank i syrefast 316



101 000 SEK /st exkl moms

Volumetric volume (L): 5.380 L

Pressure in tank: pressure and vacuum

Max. pressure (Bar): 3,50 Bar

Min. pressure (Bar): 1 Bar



Max. temperature (°C): 200 °C

Material wet parts: SS AISI 316 (V4A)

Model: vertical

Configuration: single-skin

Heat exchanger: no

Insulation: no

Mobile tank: no

Total discharge: yes

Documents included: no

Technical drawing included: no

Registration plate on the tank: yes

Flange for agitator: yes

Position of manway: headside

Outlet of tank: flange

Top: 6 mm

Cylinder: 8 mm

Bottom: 8 mm

Internal diameter tank: 1.794 mm

Cylinder height: 1.600 mm

Total height of tank: 3.140 mm

Empty weight tank: 1.200

SKU: 488019

Mer information



Beskrivelse av produkt

Materiale: Syrefast 316
Modell: Vertikal
Nyprodusert/Brukt: Brukt
Arbeidstrykk i tank: trykk og vakuum
Konfiguration: enkelthudet
Maks. arbeidstemperatur: 200 °C
Mobil tank: Nei, det er det ikke.
Omrører: Nei
Overtrykk: 3,50 bar
Total uttapping: Ja
Undertrykk (vakuum): 1 bar
Trykktank: Ja
Oppvarming/kjøling: Nei
Væskebelastet overflate: SS AISI 316 (V4A)
Volum i liter: 5380

Utstyr

Dokument finnes: Nei, det er det ikke.
Flens for omrører: Ja
Merkeskilt: Ja
Teknisk tegning finnes: Nei, det er det ikke.

Materialoversikt

Materiale: Syrefast 316

Tankdimensjoner

Sylinderhøyde: 1 600 mm
Innvendig diameter: 1 794 mm
Total høyde: 3140 mm



Tanktykkelse

Bunn: 8 millimeter

Sylinder: 8 millimeter

Topp: 6 millimeter

Mer

Isolert: Nei

Vekt: 1.200