550 liter tank i rustfritt stål 304

96 000 SEK /st exkl moms

Volumetric volume (L): 550 L
Pressure in tank: ATM - atmosferic
Max. temperature (°C): 80 °C
Material wet parts: SS AISI 304 (V2A)

PROCESSÖVERSKOTT AB

Rodervägen 57
891 78 Bonässund
info@processoverskott.se

Model: vertical

Configuration: single-skin
Heat exchanger: no
Insulation: no
Mobile tank: no
Total discharge: yes

Fixation point(s): plastic
Documents included: no
Technical drawing included: no
Registration plate on the tank: yes
Flange for agitator: no

Outlet of tank: DN50 DIN 11851
Agitator: yes
Number of revolutions: 0 -190
Power: 0,75
Internal diameter tank: 820 mm

Cylinder height: 1.034 mm
Total height of tank: 1.780 mm

SKU: 410249

Mer information

Beskrivelse av produkt

Materiale: Rustfritt stål 304
Modell: Vertikal
Nyprodusert/Brukt: Brukt
Arbeidstrykk i tank: ATM – atmosfærisk
Konfiguration: enkelthudet
Maks. arbeidstemperatur: 80 °C
Mobil tank: Nei, det er det ikke.
Øvrig informasjon: vi kan ikke gi noen garantier for omrøreren
Omrører: Ja
Total uttapping: Ja
Oppvarming/kjøling: Nei
Væskebelastet overflate: SS AISI 304 (V2A)
Volum i liter: 550

Utstyr

Dokument finnes: Nei, det er det ikke.
Flens for omrører: Nei
Merkeskilt: Ja
Teknisk tegning finnes: Nei, det er det ikke.

Materialoversikt

Materiale: Rustfritt stål 304
Festepunkt(er): plast

Tankdimensjoner

Sylinderhøyde: 1 034 mm
Innvendig diameter: 820 mm
Total høyde: 1 780 mm

Omrører

Effekt (kW): 0,75
Turtall: 0 -190

Mer
Isolert: Nei