

550 liter tank i rustfritt stål 304



104 000 SEK /st exkl moms

Volumetric volume (L): 550 L

Pressure in tank: pressure

Max. temperature (°C): 80 °C

Material wet parts: SS AISI 304 (V2A)



Model: vertical

Configuration: single-skin

Heat exchanger: no

Insulation: no

Mobile tank: no

Total discharge: yes

Volume: 3 L

Max Overpressure: 5 Bar

Max. working temperature: 80 °C

Fixation point(s): plastic

Documents included: no

Technical drawing included: no

Registration plate on the tank: yes

Flange for agitator: no

Outlet of tank: DN50 DIN 11851

Agitator: yes

Number of revolutions: 0-190

Power: 0,75

Internal diameter tank: 820 mm

Cylinder height: 1.034 mm

Total height of tank: 1.780 mm

SKU: 397487

Mer information



Beskrivelse av produkt

Materiale: Rustfritt stål 304

Modell: Vertikal

Nyprodusert/Brukt: Brukt

Arbeidstrykk i tank: ATM – atmosfærisk

Konfiguration: enkeltmantlet med varmeveksler

Maks. arbeidstemperatur: 80 °C

Mobil tank: Nei, det er det ikke.

Øvrig informasjon: vi kan ikke gi noen garantier for omrøreren

Omrører: Ja

Total uttapping: Ja

Oppvarming/kjøling: Ja

Væskebelastet overflate: SS AISI 304 (V2A)

Volum i liter: 550

Utstyr

Dokument finnes: Nei, det er det ikke.

Flens for omrører: Nei

Merkeskilt: Ja

Teknisk tegning finnes: Nei, det er det ikke.

Materialoversikt

Materiale: Rustfritt stål 304

Festepunkt(er): plast

Tankdimensjoner

Sylinderhøyde: 1 034 mm

Innvendig diameter: 820 mm

Total høyde: 1 780 mm

Omrører

Effekt (kW): 0,75

Turtall: 0-190



Mer

Isolert: Nei