5650 liters tank i syrefast 316

177 000 SEK /st exkl moms

Additional information: Pharmaceutical Chemistry; Claws made of Fe; insulating jacket has partially detached in the area of the lower base (see photos)
Volumetric volume (L): 5.650 L
Pressure in tank: pressure and vacuum
Max. pressure (Bar): 3,20 Bar

PROCESSÖVERSKOTT AB

Rodervägen 57
891 78 Bonässund
info@processoverskott.se

Läs våra köpvillkor

Min. pressure (Bar): 1 Bar

Max. temperature (°C): 200 °C
Material wet parts: SS AISI 316 (V4A)
Model: vertical
Configuration: insulated
Heat exchanger: no

Insulation: yes
Mobile tank: no
Total discharge: yes
Volume: 166 L
Max Overpressure: 6 Bar

Max. working temperature: 200 °C
Type HE on the bottom: half pipe welded onto the outside of the innertank
Type HE on the cylinder: half pipe welded onto the outside of the innertank
Documents included: no
Technical drawing included: no

Registration plate on the tank: yes
Flange for agitator: no
Position of manway: headside
Outlet of tank: 140
Agitator: yes

Number of revolutions: 55,80
Power: 2
Internal diameter tank: 1.800 mm
Outer diameter tank: 2.100 mm
Total height of tank: 3.750 mm

SKU: 487175

Rodervägen 57
891 78 Bonässund
info@processoverskott.se

Mer information

Beskrivelse av produkt

Materiale: Syrefast 316
Modell: Vertikal
Nyprodusert/Brukt: Brukt
Arbeidstrykk i tank: trykk og vakuum
Konfiguration: isolert med varmeveksler
Maks. arbeidstemperatur: 200 °C
Mobil tank: Nei, det er det ikke.
Øvrig informasjon: Farmasøytisk kjemi; Støttebraketter, Fe; isolasjonsmantelen har delvis løsnet i området nederst i bunnen (se bilder); vi kan ikke gi noen garantier om oppvarming/kjøling
Øvrig informasjon2: jakke; vi kan ikke gi noen garantier om omrøreren
Omrører: Ja
Overtrykk: 3,20 bar
Total uttapping: Ja
Undertrykk (vakuum): 1 bar
Trykktank: Ja
Oppvarming/kjøling: Ja
Væskebelastet overflate: SS AISI 316 (V4A)
Volum i liter: 5650

Utstyr

Dokument finnes: Nei, det er det ikke.
Flens for omrører: Nei
Merkeskilt: Ja
Teknisk tegning finnes: Nei, det er det ikke.

Materialoversikt

Materiale: Syrefast 316

Rodervägen 57
891 78 Bonässund
info@processoverskott.se

Tankdimensjoner
Innvendig diameter: 1 800 mm
Total høyde: 3 750 mm
Ytre diameter: 2100 mm

Omrører
Effekt (kW): 2
Turtall: 55,80

Mer
Isolert: Ja

PROCESSÖVERSKOTT AB

Rodervägen 57
891 78 Bonässund
info@processoverskott.se

Läs våra köpvillkor