

6510 liter tank i rustfritt stål 304



186 000 SEK /st exkl moms

Additional information: ethanol; a number of connections were changed by the former operator (not mentioned in the TÜV-certificates); tank on 3 support brackets made of aus Fe (not on 4 support brackets as discribed in the drawing); heating coil cylinder only in the lower cylindrical part; insulation jacket with cut-outs and dents; some residues of previous content

Volumetric volume (L): 6.510 L



Pressure in tank: pressure and vacuum

Max. pressure (Bar): 2 Bar

Min. pressure (Bar): 1 Bar

Max. temperature (°C): 165 °C

Material wet parts: SS AISI 304 (V2A)

Model: vertical

Configuration: insulated with heat-exchanger

Heat exchanger: yes

Insulation: yes

Mobile tank: no

Total discharge: yes

Volume: 34 L

Max Overpressure: 6 Bar

Max onderdruk: 1 Bar

Max. working temperature: 165 °C

Type HE on the bottom: half pipe welded onto the outside of the innertank

Type HE on the cylinder: half pipe welded onto the outside of the innertank

Heat exchanger: RVS 304

Documents included: no

Technical drawing included: no

Registration plate on the tank: yes

Flange for agitator: no

Position of manway: headside

Outlet of tank: flange DN65

Agitator: yes

Number of revolutions: 73

Power: 5,50

Top: 8 mm

Cylinder: 7 mm

Bottom: 7 mm

Internal diameter tank: 1.900 mm

Cylinder height: 1.800 mm

Total height of tank: 4.450 mm



SKU: 391067

Mer information

Beskrivelse av produkt

Materiale: Rustfritt stål 304

Modell: Vertikal

Nyprodusert/Brukt: Brukt

Arbeidstrykk i tank: trykk og vakuum

Konfiguration: isolert med varmeveksler

Maks. arbeidstemperatur: 165 °C

Mobil tank: Nei, det er det ikke.

Øvrig informasjon: etanol; en rekke tilkoblinger ble endret av den tidligere operatøren (ikke nevnt i TÜV-sertifikatene); tank på 3 støttebraketter laget av aus Fe (ikke på 4 støttebraketter som beskrevet i

Øvrig informasjon2:

Omrører: Ja

Overtrykk: 2 barer

Total uttapping: Ja

Undertrykk (vakuum): 1 bar

Trykktank: Ja

Oppvarming/kjøling: Ja

Væskebelastet overflate: SS AISI 304 (V2A)

Volum i liter: 6510

Utstyr

Dokument finnes: Nei, det er det ikke.

Flens for omrører: Nei

Merkeskilt: Ja

Teknisk tegning finnes: Nei, det er det ikke.



Materialoversikt

Materiale: Rustfritt stål 304

Tankdimensjoner

Sylinderhøyde: 1 800 mm

Innvendig diameter: 1 900 mm

Total høyde: 4 450 mm

Omrører

Effekt (kW): 5,50

Turtall: 73

Tanktykkelse

Bunn: 7 millimeter

Sylinder: 7 millimeter

Topp: 8 millimeter

Mer

Varmeveksler: RVS 304

Isolert: Ja