

689 liters tank i syrefast 316



199 000 SEK /st exkl moms

Additional information: Pharmacy; Slight metallic discoloration inside the tank; Outlet fitting incomplete

Volumetric volume (L): 689 L

Pressure in tank: pressure and vacuum

Max. pressure (Bar): 6 Bar



Min. pressure (Bar): 1 Bar

Max. temperature (°C): 150 °C

Material wet parts: SS AISI 316 (V4A)

Model: vertical

Configuration: insulated with heat-exchanger

Heat exchanger: yes

Insulation: yes

Mobile tank: no

Total discharge: yes

Volume: 63 L

Max Overpressure: 6 Bar

Max onderdruk: 1 Bar

Max. working temperature: 150 °C

Type HE on the bottom: heating/cooling jacket

Type HE on the cylinder: heating/cooling jacket

Documents included: no

Technical drawing included: no

Registration plate on the tank: yes

Flange for agitator: no

Outlet of tank: 38

Agitator: yes

Number of revolutions: 343

Power: 0,55

Top: 4,80 mm

Cylinder: 7 mm

Bottom: 5,20 mm

Internal diameter tank: 800 mm

Outer diameter tank: 950 mm

Cylinder height: 1.180 mm

Total height of tank: 2.400 mm

SKU: 412139



Mer information

Beskrivelse av produkt

Materiale: Syrefast 316

Modell: Vertikal

Nyprodusert/Brukt: Brukt

Arbeidstrykk i tank: trykk og vakuum

Konfiguration: isolert med varmeveksler

Maks. arbeidstemperatur: 150 °C

Mobil tank: Nei, det er det ikke.

Øvrig informasjon: Apotek; Lett metallisk misfarging inne i tanken; Utløpsarmatur ufullstendig; vi kan ikke gi noen garantier for varme-/kjølekappen; vi kan ikke gi noen garantier for omrøreren

Omrører: Ja

Overtrykk: 6 barer

Total uttapping:

Undertrykk (vakuum): 1 bar

Trykktank: Ja

Oppvarming/kjøling: Ja

Væskebelastet overflate: SS AISI 316 (V4A)

Volum i liter: 689

Utstyr

Dokument finnes: Nei, det er det ikke.

Flens for omrører: Nei

Merkeskilt: Ja

Teknisk tegning finnes: Nei, det er det ikke.

Materialoversikt

Materiale: Syrefast 316



Tankdimensjoner

Sylinderhøyde: 1 180 mm
Innvendig diameter: 800 mm
Total høyde: 2 400 mm
Ytre diameter: 950 mm

Omrører

Effekt (kW): 0,55
Turtall: 343

Tanktykkelse

Bunn: 5,20 mm
Sylinder: 7 millimeter
Topp: 4,80 mm

Mer

Isolert: Ja