

7040 liters tank i syrefast 316



277 000 SEK /st exkl moms

Additional information: Saline solution; Slight metallic discoloration inside; The production and documentation drawings are available from the manufacturer and can be purchased separately from there; some residues of previous content; bump at the insulation jacket; pipe end cut flush

Volumetric volume (L): 7.040 L

Pressure in tank: pressure and vacuum



Max. pressure (Bar): 2,50 Bar

Min. pressure (Bar): 1 Bar

Max. temperature (°C): 140 °C

Material wet parts: SS AISI 316 (V4A)

Model: vertical

Configuration: insulated with heat-exchanger

Heat exchanger: yes

Insulation: yes

Mobile tank: no

Total discharge: yes

Volume: 176 L

Max Overpressure: 2 Bar

Max onderdruk: 1 Bar

Max. working temperature: 140 °C

Type HE on the bottom: heating/cooling jacket

Documents included: no

Technical drawing included: no

Registration plate on the tank: yes

Flange for agitator: no

Position of manway: in the bottom

Outlet of tank: 38

Internal diameter tank: 1.880 mm

Outer diameter tank: 2.100 mm

Cylinder height: 2.000 mm

Total height of tank: 3.700 mm

Empty weight tank: 1.120

SKU: 402887



Mer information

Beskrivelse av produkt

Materiale: Syrefast 316

Modell: Vertikal

Nyprodusert/Brukt: Brukt

Arbeidstrykk i tank: trykk og vakuum

Konfiguration: isolert med varmeveksler

Maks. arbeidstemperatur: 140 °C

Mobil tank: Nei, det er det ikke.

Øvrig informasjon: Saltoppløsning; Lett metallisk misfarging innvendig; Produksjons- og dokumentasjonstegninger er tilgjengelige fra produsenten og kan kjøpes separat derfra; noen rester av

Øvrig informasjon2: tidligere innhold; støt ved isolasjonskappen; rørenden kuttet i flukt; vi kan ikke gi noen garantier for varme- / kjølekappen

Omrører: Nei

Overtrykk: 2,50 bar

Total uttapping: Ja

Undertrykk (vakuum): 1 bar

Trykktank: Ja

Oppvarming/kjøling: Ja

Væskebelastet overflate: SS AISI 316 (V4A)

Volum i liter: 7040

Utstyr

Dokument finnes: Nei, det er det ikke.

Flens for omrører: Nei

Merkeskilt: Ja

Teknisk tegning finnes: Nei, det er det ikke.

Materialoversikt

Materiale: Syrefast 316



Tankdimensjoner

Sylinderhøyde: 2 000 mm

Innvendig diameter: 1 880 mm

Total høyde: 3 700 mm

Ytre diameter: 2100 mm

Mer

Isolert: Ja

Vekt: 1.120