710 liters tank i rustfritt stål 304



60 000 SEK /st exkl moms

item available on order

Article type: brand new fermentation tank - type CCT-HL
Additional information: Included in the price: cip spraybol, thermometer, sample valve. In option: butterfly valve, airlock (see options); Ra=<0.8µm
Volumetric volume (L): 710 L
Max. density P (kg/m³): 1.050
Ra inner weld: 0,80

Finish stainless steel: 2b
Pressure in tank: pressure

PROCESSÖVERSKOTT AB

Rodervägen 57
891 78 Bonässund
info@processoverskott.se

Max. pressure (Bar): 0,50 Bar
Max. temperature (°C): 30 °C
Material wet parts: SS AISI 304 (V2A)

Model: vertical
Configuration: single jacketed with heat-exchanger
Heat exchanger: yes
Insulation: no
Mobile tank: no

Top type: conical
Shape of tank: cylindrical
Bottom type: strong conical 60 °
Total discharge: yes
Fixation points: 3 adjustable feet

Legs: Set of baseplates and adjusting pieces included
Type of HE on the cylinder: dimple-jacket
Position HE: the middle part of the cilinder
Height HE: 500 mm
Number of sections: 1

Water pressure HE: 3 Bar
Contact surface cylinder: 1,20 m²
Connection HE: 1" BSP
Working temperature HE cylinder: -10 °C
Heat exchanger: RVS 304

Manway(s): RVS 304
Gasket manway(s): EPDM
Fixation point(s): RVS 304
Suitable for food industry: yes
Documents included: yes, optional

Technical drawing included: yes
Registration plate on the tank: yes
Flange for agitator: no
Number of manways: 1
Position of manway: at the top

Rodervägen 57
891 78 Bonässund
info@processoverskott.se

Height manhole 1 (mm): 500 mm
CIP spray ball: yes
Tank outlet: inside Ø 32 mm
Outlet type: DIN32676 CLAMP FERRULE
Total outlet valve: no, optional

Adjustable legs: yes
Agitator: no
Top: 2 mm
Cylinder: 2 mm
Bottom: 2 mm

Internal diameter tank: 840 mm
Distance from outlet to ground: 200 mm
Outer diameter tank: 846 mm
Cylinder height: 1.000 mm
Height of bottom: 765 mm

Feet height: 965 mm
Total height of tank: 2.152 mm
Empty weight tank: 120

SKU: 377312

Mer information

Beskrivelse av produkt

Næringsmiddelgodkjent: Ja
Materiale: Rustfritt stål 304
Modell: Vertikal
Nyprodusert/Brukt: Nyprodusert
Arbeidstrykk i tank: trykk
Finish rustfritt stål: 2b
Konfiguration: enkeltmantlet med varmeveksler
Maks. arbeidstemperatur: 30 °C
Maksimal tetthet for produktet: 1050
Mobil tank: Nei, det er det ikke.
Øvrig informasjon: Inkludert i prisen: cip spraybol, termometer, prøveventil. Som tilvalg: spjeldventil, luftsluse (se tilvalg); Ra=<0,8µm
Omrører: Nei
Overtrykk: 0,50 bar
Ra innvendig sveis: 0,80
Tankens form: sylindrisk
Total uttapping:
Type bunn:
Trykktank: Ja
Oppvarming/kjøling: Ja
Væskebelastet overflate: SS AISI 304 (V2A)
Volum i liter: 710

Utstyr

Flens for omrører: Nei
Merkeskilt: Ja
Næringsmiddelgodkjent: Ja
Tankutløp: innvendig Ø 32 mm
Teknisk tegning finnes: Ja
Utløpstype: DIN32676 KLEMMEHYLSE

Materialoversikt

Materiale: Rustfritt stål 304
Festepunkt(er): RVS 304

Tankdimensjoner

Sylinderhøyde: 1 000 mm
Høyde på ben: 965 mm
Innvendig diameter: 840 mm
Mål utløp til bakken: 200 mm
Total høyde: 2,152 mm
Ytre diameter: 846 mm

Varmevekslere

Tilkobling varmeveksler: 1" BSP
Arbeidstemperatur varmeveksler sylinder: -10 °C
Høyde varmeveksler: 500 mm
Kontaktflate sylinder: 1,20 m²
Posisjon varmeveksler: den midtre delen av cilinderen
Type varmeveksler på sylinder: dimple jakke
Vanntrykk varmeveksler: 3 barer

Tanktykkelse

Bunn: 2 millimeter
Sylinder: 2 millimeter
Topp: 2 millimeter

Mer

Varmeveksler: RVS 304
Isolert: Nei
Vekt: 120