710 liters tank i syrefast 316

177 000 SEK /st exkl moms

Additional information: pharmacy
Volumetric volume (L): 710 L
Pressure in tank: pressure and vacuum
Max. pressure (Bar): 4 Bar

PROCESSÖVERSKOTT AB

Rodervägen 57
891 78 Bonässund
info@processoverskott.se

Läs våra köpvillkor

Min. pressure (Bar): 1 Bar

Max. temperature (°C): 130 °C
Material wet parts: SS AISI 316 (V4A)
Model: vertical
Configuration: insulated with heat-exchanger
Heat exchanger: yes

Insulation: yes
Mobile tank: no
Total discharge: yes
Volume: 55 L
Max Overpressure: 6 Bar

Max onderdruk: 1 Bar
Max. working temperature: 130 °C
Type HE on the bottom: heating/cooling jacket
Type HE on the cylinder: heating/cooling jacket
Heat exchanger: RVS 304

Documents included: no
Technical drawing included: no
Registration plate on the tank: yes
Flange for agitator: no
Position of manway: in the bottom

Outlet of tank: 25
Agitator: yes
Number of revolutions: 900
Power: 0,55
Cylinder: 5 mm

Bottom: 5,80 mm
Internal diameter tank: 900 mm
Outer diameter tank: 1.050 mm
Cylinder height: 900 mm
Total height of tank: 2.150 mm

SKU: 394502

PROCESSÖVERSKOTT AB

Rodervägen 57
891 78 Bonässund
info@processoverskott.se

Läs våra köpvillkor

Mer information

Beskrivelse av produkt

Materiale: Syrefast 316
Modell: Vertikal
Nyprodusert/Brukt: Brukt
Arbeidstrykk i tank: trykk og vakuum
Konfiguration: isolert med varmeveksler
Maks. arbeidstemperatur: 130 °C
Mobil tank: Nei, det er det ikke.
Øvrig informasjon: apotek; vi kan ikke gi noen garantier for varme-/kjølekappen; vi kan ikke gi noen garantier for omrøreren
Omrører: Ja
Overtrykk: 4 barer
Total uttapping: Ja
Undertrykk (vakuum): 1 bar
Trykktank: Ja
Oppvarming/kjøling: Ja
Væskebelastet overflate: SS AISI 316 (V4A)
Volum i liter: 710

Utstyr

Dokument finnes: Nei, det er det ikke.
Flens for omrører: Nei
Merkeskilt: Ja
Teknisk tegning finnes: Nei, det er det ikke.

Materialoversikt

Materiale: Syrefast 316

Rodervägen 57
891 78 Bonässund
info@processoverskott.se

Tankdimensjoner
Sylinderhøyde: 900 mm
Innvendig diameter: 900 mm
Total høyde: 2 150 mm
Ytre diameter: 1 050 mm

Omrører
Effekt (kW): 0,55
Turtall: 900

Tanktykkelse
Bunn: 5,80 mm
Sylinder: 5 mm

Mer
Varmeveksler: RVS 304
Isolert: Ja

PROCESSÖVERSKOTT AB

Rodervägen 57
891 78 Bonässund
info@processoverskott.se

Läs våra köpvillkor