

720 liters tank i syrefast 316



57 000 SEK /st exkl moms

Additional information: chemistry; 3 claws made of Fe; screws of the top flange are mostly missing; motor-/gear is missing

Volumetric volume (L): 720 L

Pressure in tank: pressure

Max. pressure (Bar): 2 Bar



Min. pressure (Bar): 2 Bar

Max. temperature (°C): 150 °C

Material wet parts: SS AISI 316 (V4A)

Model: vertical

Configuration: single-skin

Heat exchanger: no

Insulation: no

Mobile tank: no

Total discharge: yes

Volume: 52 L

Max Overpressure: 6 Bar

Max. working temperature: 200 °C

Type HE on the bottom: half pipe welded onto the outside of the innertank

Type HE on the cylinder: half pipe welded onto the outside of the innertank

Heat exchanger: RVS 316

Documents included: no

Technical drawing included: no

Registration plate on the tank: yes

Flange for agitator: no

Outlet of tank: available

Agitator: yes

Top: 8,20 mm

Cylinder: 6,20 mm

Bottom: 5,90 mm

Internal diameter tank: 790 mm

Cylinder height: 1.220 mm

Total height of tank: 2.250 mm

SKU: 391415



Mer information

Beskrivelse av produkt

Materiale: Syrefast 316

Modell: Vertikal

Nyprodusert/Brukt: Brukt

Arbeidstrykk i tank: trykk

Konfiguration: enkeltmantlet med varmeveksler

Maks. arbeidstemperatur: 150 °C

Mobil tank: Nei, det er det ikke.

Øvrig informasjon: kjemi; 3 støttebraketter Fe; skruene på den øvre bunnflensen mangler for det meste; motor-/gear mangler; vi kan ikke gi noen garantier for røreverket

Omrører: Ja

Overtrykk: 2 barer

Total uttapping: Ja

Undertrykk (vakuum):

Trykktank: Ja

Oppvarming/kjøling: Ja

Væskebelastet overflate: SS AISI 316 (V4A)

Volum i liter: 720

Utstyr

Dokument finnes: Nei, det er det ikke.

Flens for omrører: Nei

Merkeskilt: Ja

Teknisk tegning finnes: Nei, det er det ikke.

Materialoversikt

Materiale: Syrefast 316



Tankdimensjoner

Sylinderhøyde: 1 220 mm

Innvendig diameter: 790 mm

Total høyde: 2 250 mm

Tanktykkelse

Bunn: 5,90 mm

Sylinder: 6,20 mm

Topp: 8,20 mm

Mer

Varmeveksler: RVS 316

Isolert: Nei