

7250 liters tank i syrefast 316



90 000 SEK /st exkl moms

Additional information: chemistry; Vessel hangs on crossbar made of Fe; outlet fitting incomplete; manhole cover is missing

Volumetric volume (L): 7.250 L

Pressure in tank: pressure

Max. temperature (°C): 100 °C



Material wet parts: SS AISI 316 (V4A)

Model: vertical

Configuration: single-skin

Heat exchanger: no

Insulation: no

Mobile tank: no

Total discharge: yes

Max Overpressure: 5 Bar

Max. working temperature: 160 °C

Type HE on the bottom: half pipe welded onto the outside of the innertank

Type HE on the cylinder: half pipe welded onto the outside of the innertank

Heat exchanger: RVS 304

Documents included: no

Technical drawing included: no

Registration plate on the tank: yes

Flange for agitator: no

Position of manway: headside

Outlet of tank: flange DN80

Agitator: yes

Number of revolutions: 125

Power: 4

Top: 4 mm

Cylinder: 5 mm

Bottom: 5 mm

Internal diameter tank: 2.000 mm

Cylinder height: 2.000 mm

Total height of tank: 3.700 mm

SKU: 394667



Mer information

Beskrivelse av produkt

Materiale: Syrefast 316

Modell: Vertikal

Nyprodusert/Brukt: Brukt

Arbeidstrykk i tank:

Konfiguration: enkeltmantlet med varmeveksler

Maks. arbeidstemperatur: 100 °C

Mobil tank: Nei, det er det ikke.

Øvrig informasjon: kjemi; tankmontering: travers Fe; utløpsarmatur ufullstendig; kumløkk mangler; vi kan ikke gi noen garantier om omrøreren

Omrører: Ja

Total uttapping:

Oppvarming/kjøling: Ja

Væskebelastet overflate: SS AISI 316 (V4A)

Volum i liter: 7250

Utstyr

Dokument finnes: Nei, det er det ikke.

Flens for omrører: Nei

Merkeskilt: Ja

Teknisk tegning finnes: Nei, det er det ikke.

Materialoversikt

Materiale: Syrefast 316

Tankdimensjoner

Sylinderhøyde: 2 000 mm

Innvendig diameter: 2 000 mm

Total høyde: 3 700 mm

**Omrører**

Effekt (kW): 4

Turtall: 125

Tanktykkelse

Bunn: 5 mm

Sylinder: 5 mm

Topp: 4 mm

Mer

Varmeveksler: RVS 304

Isolert: Nei