

750 liters tank i rustfritt stål 304



108 000 SEK /st exkl moms

item available on order

Article type: brand new transport tank

Volumetric volume (L): 750 L

Max. density P (kg/m³): 1.200

Ra inner weld: 0,80

Pressure in tank: pressure

Design pressure (Bar): 3,40 Bar

Max. pressure (Bar): 2 Bar

Min. pressure (Bar): -0,15 Bar



Max. temperature (°C): 130 °C

Min. temperature (°C): 10 °C

Material wet parts: SS AISI 304 (V2A)

Model: vertical

Configuration: single jacketed with heat-exchanger

Heat exchanger: yes

Insulation: no

Mobile tank: no

Top type: dished

Shape of tank: cylindrical

Bottom type: strong conical 45 °

Total discharge: yes

Fixation points: 4 non adjustable feet

Type of HE on the cylinder: dimple-jacket

Position HE: the complet cilinder

Height HE: 525 mm

Number of sections: 1

Water pressure HE: 3 Bar

Hydraulic test pressure: 5,20 Bar

Working temperature HE cylinder: 80 °C

Type of HE on the bottom: dimple-jacket

Heat exchanger bottom connected with cylinder: yes

Water pressure HE: 3 Bar

Hydraulic test pressure: 5,20 Bar

Working temperature HE bottom: 80 °C

Heat exchanger: RVS 304

Manway(s): RVS 304

Gasket manway(s): EPDM

Valve: RVS 304

Gasket shut-off valve (mat): EPDM

Fixation point(s): RVS 304

Suitable for food industry: yes

Documents included: yes, optional



Technical drawing included: yes
Registration plate on the tank: yes
Flange for agitator: no
Number of manways: 1

Position of manway: at the top
Height manhole 1 (mm): 400 mm
Tank outlet: inside Ø 32 mm
Outlet type: DIN11851 male
Total outlet valve: yes

Agitator: no, optional
Top: 2 mm
Cylinder: 2 mm
Bottom: 2,50 mm
Internal diameter tank: 1.000 mm

Distance from outlet to ground: 200 mm
Outer diameter tank: 1.005 mm
Cylinder height: 645 mm
Total height of tank: 1.650 mm
Empty weight tank: 180

SKU: 418007

Mer information



Beskrivelse av produkt

Næringsmiddelgodkjent: Ja
Materiale: Rustfritt stål 304
Modell: Vertikal
Nyprodusert/Brukt: Nyprodusert
Arbeidstrykk i tank: trykk
Designtrekk for tanken: 3,40 bar
Konfiguration: enkeltmantlet med varmeveksler
Maks. arbeidstemperatur: 130 °C
Maksimal tetthet for produktet: 1200
Min. arbeidstemperatur: 10 °C
Mobil tank: Nei, det er det ikke.
Omrører: Nei
Overtrykk: 2 barer
Ra innvendig sveis: 0,80
Tankens form: sylindrisk
Total uttapping: Ja
Type bunn: Sterk konisk 45°.
Undertrykk (vakuum): -0,15 Bar
Trykktank: Ja
Oppvarming/kjøling: Ja
Væskebelastet overflate: SS AISI 304 (V2A)
Volum i liter: 750

Utstyr

Flens for omrører: Nei
Merkeskilt: Ja
Næringsmiddelgodkjent: Ja
Tankutløp: innvendig Ø 32 mm
Teknisk tegning finnes: Ja
Utløpstype: DIN11851 hann
Utløpsventil: Ja



Materialoversikt

Materiale: Rustfritt stål 304

Festepunkt(er): RVS 304

Tankdimensjoner

Sylinderhøyde: 645 mm

Innvendig diameter: 1 000 mm

Mål utløp til bakken: 200 mm

Total høyde: 1 650 mm

Ytre diameter: 1.005 mm

Varmevekslere

Arbeidstemperatur varmeveksler sylinder: 80 °C

Arbeidstemperatur varmeveksler bunn: 80 °C

Høyde varmeveksler: 525 mm

Hydraulisk prøvetrykk bunn: 5,20 bar

Hydraulisk prøvetrykk: 5,20 bar

Posisjon varmeveksler: den komplette sylindren

Type varmeveksler på sylinder: dimple jakke

Type varmeveksler på bunn: dimple jakke

Vanntrykk varmeveksler: 3 barer

Vanntrykk varmeveksler bunn: 3 barer

Tanktykkelse

Bunn: 2,50 mm

Sylinder: 2 millimeter

Topp: 2 millimeter

Mer

Varmeveksler: RVS 304

Isolert: Nei

Vekt: 180