

750 liters tank i syrefast 316



106 000 SEK /st exkl moms

Additional information: Pharmacy; Attention: The information on the operating pressure of the tank and double jacket as well as the maximum operating temperature of the tank was taken from a drawing that can be assigned to the tanks using the inventory number; 1 tank with slightly stronger dents in the insulation jacket (see photos); dents at the insulation jacket

Volumetric volume (L): 750 L



Pressure in tank: pressure and vacuum

Max. pressure (Bar): 1,80 Bar

Min. pressure (Bar): 1 Bar

Max. temperature (°C): 121 °C

Material wet parts: SS AISI 316 (V4A)

Model: vertical

Configuration: insulated with heat-exchanger

Heat exchanger: yes

Insulation: yes

Mobile tank: no

Total discharge: yes

Max Overpressure: 2 Bar

Type HE on the bottom: heating/cooling jacket

Type HE on the cylinder: heating/cooling jacket

Documents included: no

Technical drawing included: no

Registration plate on the tank: no

Flange for agitator: no

Outlet of tank: 48

Top: 5 mm

Cylinder: 6 mm

Bottom: 6 mm

Internal diameter tank: 1.138 mm

Outer diameter tank: 1.290 mm

Cylinder height: 580 mm

Total height of tank: 2.100 mm

SKU: 421808



Mer information

Beskrivelse av produkt

Materiale: Syrefast 316

Modell: Vertikal

Nyprodusert/Brukt: Brukt

Arbeidstrykk i tank: trykk og vakuum

Konfiguration: isolert med varmeveksler

Maks. arbeidstemperatur: 121 °C

Mobil tank: Nei, det er det ikke.

Øvrig informasjon: Apotek; OBS: Informasjonen om driftstrykket til tanken og den doble kappen samt tankens maksimale driftstemperatur ble hentet fra en tegning som kan tilordnes

Øvrig informasjon2:

Omrører: Nei

Overtrykk: 1,80 bar

Total uttapping: Ja

Undertrykk (vakuum): 1 bar

Trykktank: Ja

Oppvarming/kjøling: Ja

Væskebelastet overflate: SS AISI 316 (V4A)

Volum i liter: 750

Utstyr

Dokument finnes: Nei, det er det ikke.

Flens for omrører: Nei

Merkeskilt: Nei, det er det ikke.

Teknisk tegning finnes: Nei, det er det ikke.

Materialoversikt

Materiale: Syrefast 316



Tankdimensjoner

Sylinderhøyde: 580 mm

Innvendig diameter: 1.138 mm

Total høyde: 2100 mm

Ytre diameter: 1 290 mm

Tanktykkelse

Bunn: 6 millimeter

Sylinder: 6 millimeter

Topp: 5 mm

Mer

Isolert: Ja